



Your technology partner for cost-effective machining

TURNING



When there's something more between you and us:
That's the MAPAL effect.

You

are looking for a technology
expert who thinks the way
you think?

We

Partnership

employ all our resources
for the solution of your
tasks.



Machine and plant
engineering



Shipbuilding



Rail transport



Power generation




Aerospace



Automotive



Medical technology



Tool and process solutions combined with comprehensive services

We see ourselves as a technology partner, supporting you with the development of efficient and resource-saving manufacturing processes using standard tools, individual tool concepts and the optimisation of tool details. Our tools satisfy all the requirements on process reliability, precision and simple handling. How? Using advanced development and design methods as well as production using the latest manufacturing facilities.

You do not just need the optimal tool for your task, you are also looking for a partner who takes over the entire planning and management of your process? We are also there for you in this situation. We support you during all production phases and keep your manufacturing at the top level: highly productive, cost-effective and reliable. We also offer you complete networked solutions for all peripheral tasks related to the actual machining process.



Reaming and fine
boring



Drilling from the solid,
boring and countersinking



Milling



Turning



Actuating



Clamping



Setting, measuring and
dispensing



Services



CONTENTS

01 Introduction

Turning competence	06
--------------------	----

02 Hard turning innovations

PcBN round inserts with indexing	10
----------------------------------	----

Scroll-free turning	18
---------------------	----

VersaCut grooving and turning system	24
--------------------------------------	----

03 Extremely hard cutting materials

Introduction to extremely hard cutting materials, designation key	40
-------------------------------------------------------------------	----

PcBN indexable inserts	44
------------------------	----

PCD indexable inserts	66
-----------------------	----

04 HSK-T

Tools with HSK-T connection	92
-----------------------------	----

Conversion systems and adapters to HSK-T	132
------------------------------------------	-----

05 Technical appendix

Description HSK-T	156
-------------------	-----

Handling notes VersaCut	160
-------------------------	-----

Cutting data recommendation PcBN cutting materials	161
----------------------------------------------------	-----

Cutting data recommendation PCD cutting materials	161
---------------------------------------------------	-----

TURNING COMPETENCE

Rational, exact and efficient

Building on extensive experience with the extremely hard cutting materials PcbN and PCD from the area of boring, milling and reaming, MAPAL has also obtained a profound understanding of the turning process. A clear focus here is on hard turning.

The range from MAPAL includes special tool solutions for scroll-free turning for complete machining of sealing faces, bearing surfaces and bearing seats on the lathe. This saves time-consuming re-clamping of the workpieces on grinding machines.


To utilise optimally costly PcbN round inserts, MAPAL has developed a system with indexable round inserts that makes simply defined rotation of the insert in the machine possible.

In this way the insert can be utilised optimally. Maximum stability during hard grooving with PcbN is ensured by the grooving system VersaCut. It offers the optimal prerequisites for the special requirements of hard machining.

Today MAPAL offers a broad selection of PCD and PcbN-tipped indexable inserts for hard turning with an extensive selection of cutting materials and cutting edge design. In addition, the MAPAL portfolio includes a broad HSK-T program with turning holders for the connections HSK-T40, 63 and 100. A complete machine-specific range of conversion systems makes it possible to integrate the advantages of the HSK-T connection also in an existing environment.

Hard turning innovations

PcbN round inserts with indexing	Scroll-free turning	VersaCut grooving and turning system
		
<p>Costly cutting material such as PcbN must be utilised to the maximum. At the same time the reliability and stability of the processes must not be impaired. The MAPAL system for hard turning with indexable PcbN round inserts ensures easy handling and optimal cutting material utilisation.</p>	<p>With the scroll-free turning process, which is a special form of kinematics between the rotating workpiece and a rotating tool, grinding is not required. Parts can be fully machined on the lathe. In comparison to conventional machining, this turning method makes it possible to reduce machining times by more than 70 % - with increased process reliability and tool life.</p>	<p>The flexible grooving system VersaCut offers the optimal prerequisites for the special requirements of hard machining. The PcbN-tipped inserts are clamped extremely stably. The system covers inserts of varying widths and shapes for recessing and groove turning, as well as for machining threads.</p>



Extremely hard cutting materials HSK-T

PcBN and PCD indexable inserts



Building on its existing knowledge of boring, milling and reaming, MAPAL has developed PCD and PcBN-tipped indexable inserts for applications with particularly high requirements. The two extremely hard cutting materials polycrystalline diamond (PCD) and polycrystalline cubic boron nitride (PcBN) are indispensable in today's production world.

Tools with HSK-T connection



MAPAL offers a complete turning holder programme in the sizes HSK-T 40, HSK-T 63 and HSK-T 100. In this way almost all turning methods are covered. The tools can be operated with HSK-A tool changers. This aspect ensures a high degree of flexibility.

Conversion systems and adapters to HSK-T




HSK-T conversion systems make it possible to integrate the advantages of the HSK-T connection in an existing environment. The process can be specifically optimised using the conversion systems to HSK-T, as due to the high accuracy when changing the tools, times for setting up or breaking-in are practically not required.

HARD TURNING INNOVATIONS

PcBN round inserts with indexing, scroll-free turning and VersaCut







PcBN ROUND INSERTS WITH INDEXING

Introduction

Product description _____ 12

Overview of the range

Selection of PcBN round insert system with indexing _____ 14

PcBN ROUND INSERTS WITH INDEXING

Sustainability, cost-effectiveness and efficiency are the keywords in manufacturing today. Costly cutting material such as PcBN must be utilised to the maximum without reducing the reliability and stability of the processes.


MAPAL has developed a system with indexing for hard turning to utilise PcBN round inserts to the maximum. The indexing is optimally matched to the cutting depth by means of differently defined graduations. Slightly undoing the stable clamping is sufficient to rotate the insert to the next position in a defined manner. This action can also be undertaken in the machine. The spring pin engages exactly in the indexing during this process. As a consequence changing times are shortened and the efficiency increased without reducing performance or stability compared to monolithic tools.

An optimally matched spindle system is ensured by the selection of spindles for roughing and finishing (depending on the stock removal) and indexable inserts. The basic holder remains the same here.

AT A GLANCE

- Defined rotation of the indexable insert
- Possible to change in the machine
- Indexable inserts for hardened steel and cast iron
- Varying indexing
- Maximum cutting material utilisation
- Indexable inserts for continuous and interrupted cut

Tool features in detail



1 Spindle

2 Backing plate with driving element

3 Indexable insert with bore for indexing on both sides

4 Clamping plate

5 Threaded spindle

6 Spring pin






Easy handling



The defined rotation of the indexable insert is undertaken in the machine. The clamping plate is undone slightly using a hex-wrench and then the spindle can be rotated to the next position for use. After tightening the clamping plate using the hex-wrench, the tool is ready for use again.

Optimal cutting material utilisation



The standard programme covers spindles with different spacings. The selection of different spindles for roughing and finishing (stock removal) and indexable inserts for combined longitudinal and face turning ensures the spindle system is always optimally matched.

Tool configuration for round insert systems with indexing

1 Shank/machine interface



2 Machining-specific indexing



Select by holder size


Square holder		
Holder size	Insert size	Design
20x20	12	L
	09	R
25x25	12	L
	09	R

Other shank connections, e.g. HSK-T, VDI, Capto or UT40 can be ordered on request.


Selection of the optimal indexing

Example illustration of the dependency of feed, cutting depth and insert diameter. The values shown are guideline values and only apply for longitudinal machining or face machining.

Round insert RNGX09



Round insert RNGX12



20-position indexing	15-position indexing	10-position indexing	8-position indexing	6-position indexing	4-position indexing

Below the table, a horizontal bar indicates the range of feed rates and cutting depths:

- f max. (top edge)
- a_p min. (bottom edge)
- f min. (bottom edge)
- a_p max. (bottom edge)

3

Material and machining



Continuous cut

Interrupted cut and
large stock removal fluctuations

Selection of the cutting material based on workpiece material, geometry and cutting conditions

			Cutting material	FP834	FP853	FU430		FU872
			Machining	General turning	General turning	Finish turning	Rough turning	
			Cutting edge design	S14	S12	E01	T51	
			Cutting conditions	☒	●	●	☒	●
Machining group	Material	Strength/hardness						
K	K1 K1.1 Cast iron with lamellar graphite (grey cast iron), GJL	< 300 N/mm ²				★	★	★
K	K2.1 Cast iron with spheroidal graphite, GJS	< 500 N/mm ²	■			★	★	
K	K2.2 Cast iron with spheroidal graphite, GJS	500-800 N/mm ²	■	★				
K	K2.3 Cast iron with spheroidal graphite, GJS	> 800 N/mm ²	★	■				
S	S2.1 Titanium, titanium alloys	< 1200 N/mm ²	■			■	■	
S	S2.2 Titanium, titanium alloys	> 1200 N/mm ²	■			■	■	
S	S4.1 High-temperature super alloy Ni, Co and Fe-based					★	★	
H	H1.1 Hardened steel/cast steel	52-58 HRC	★	■	★			
H	H1.2 Hardened steel/cast steel	58-63 HRC	★	■	★			
H	H1.3 Hardened steel/cast steel	> 63 HRC			★			
H	H2.1 Wear-resistant cast iron/chilled cast iron, GJN					★	★	
Sintered steel		e.g. SintD32	> 60 HRC			★	★	

★ First choice ■ Alternative

Standard holder

For round inserts with indexing





Figure: Right design



Shank design	Size	l_1	l_2	l_3	l_4	Direction of rotation	Insert	Order No.
Square shank	20x20	150	50	20	27,7	Right	RNGX 0903	30578841
Square shank	20x20	150	50	20	27,7	Left	RNGX 0903	30578779
Square shank	20x20	150	50	20	29,3	Right	RNGX 1204	30578822
Square shank	20x20	150	50	20	29,3	Left	RNGX 1204	30578719
Square shank	25x25	150	50	20	32,8	Right	RNGX 0903	30564368
Square shank	25x25	150	50	20	32,8	Left	RNGX 0903	30567505
Square shank	25x25	150	50	20	34,4	Right	RNGX 1204	30567285
Square shank	25x25	150	50	20	34,4	Left	RNGX 1204	30568897

Spindle with indexing

For round inserts with indexing


Holder size	20-position indexing	15-position indexing	10-position indexing	8-position indexing	6-position indexing	4-position indexing
-------------	----------------------	----------------------	----------------------	---------------------	---------------------	---------------------



20x20	30578741	30579074	30579066	30588629	30588628	30588626
25x25	30551299	30551332	30551070	30588624	30588621	30588618

RNGX

PcBN indexable insert



Specification	Dimensions		FU430		FU872	FP823	FP834	
	d	s	E01	T51	S09	T13	S14	
RNGX090300...N-OAS	9,52	3,18			30815401	30815398		
RNGX090300...N-OAF	9,52	3,18					30815400	
RNGX090300...N-OAE	9,52	3,18	30815387	30815388				
RNGX120400...N-OAS	12,7	4,76			30815379	30815377		
RNGX120400...N-OAF	12,7	4,76					30815380	
RNGX120400...N-OAE	12,7	4,76	30815384	30815385				

Spare parts

Parts included

	Model	Order No.
	Threaded spindle	10036727
	Torx screw	10105075
	Backing plate for RNGX09	30551467
	Backing plate for RNGX12	30567325
	Spring pin	30550948
	Clamping plate	30551046

Dimensions in mm.





SCROLL-FREE TURNING

Introduction

Product description 20

Overview of the range

Systems for scroll-free turning 22

SCROLL-FREE TURNING


Complete machining of sealing faces, bearing surfaces and bearing seats on the lathe



Radial seals, bearing surfaces and bearing seats on shafts and axles must be machined absolutely cylindrically and scroll-free. To address these tight tolerance requirements, parts are moved from the lathe and re-clamped on the grinding machine and finish machined there. With the scroll-free turning process, which represents a special form of kinematics between the workpiece and tool, grinding is not required.

Parts can be completely machined on the lathe. Re-clamping and downtimes are no longer necessary. As a consequence there are also no disposal costs for the grinding slurry. The sealing faces produced using this method are scroll-free and do not affect the assembly or, above all, the sealing functions of the seals in contact, as is normally the case with hard-turned surfaces. To obtain not only scroll-free but also absolutely cylindrical surfaces, on the one hand the machines must be very accurate and be able to undertake correspondingly

controlled movements. On the other hand, the tools must be equipped with a highly precise cutting edge that is stably clamped.

In the area of bore fine machining MAPAL has extensive experience with such cutting systems also for large contact lengths and corresponding tools developed for the scroll-free turning process. Compact holders are used to hold ground inserts with the highest accuracy. Also important during the machining is the robust clamping jaw in conjunction with the clamping groove on the insert. Together with the choice of the optimal PcbN grade and the edge preparation, a tool concept for the highest performance during scroll-free hard turning is available. The product range includes VDI and HSK-T connections designed as single holders with one insert or as double holders with two inserts. Depending on the workpiece, the MAPAL tools can be mounted vertically or horizontally.



**Gearwheel machining (internal machining, vertical)****Shaft machining (horizontal)**

1 Tools with one blade machine the workpiece, depending on the stock removal, in one machining step or in two machining steps with different stock for pre and finish machining.

2 With double holders one insert is used for pre-machining and one (identical) insert for the finishing operation. This configuration increases the process reliability and results in an increase in the tool life.

Scroll-free turning

Tool configuration for external machining

Tools for scroll-free turning from MAPAL are designed to suit the specific application.

The following features are required for the configuration.

1

Information on the machine
(customer)

Description of machine and connection

Machine * Connection

5-axis lathe	Connec-tion	Tool holder
	VDI	Monolithic holder Square holder Module holder
	HSK	Monolithic holder
	Capto	Monolithic holder

* Please note:

The machine kinematics during scroll-free turning define the geometry of the cutting edge. Existing proprietary rights must also be taken into account during design such that the machine type must be stated with enquiries.

2

Information on the part
(customer)

Description of the surface finish requirement as well as on the materials to be machined, hardness, stock removal and machining length

Workpiece material selection
in acc. with MAPAL machining groups


Machining group	Material	Strength/hardness
K	K1 K1.1 Cast iron with lamellar graphite (grey cast iron), GJL	< 300 N/mm ²
	K2 K2.1 Cast iron with spheroidal graphite, GJS	< 500 N/mm ²
S	S2.1 Titanium, titanium alloys	< 1200 N/mm ²
	S2.2 Titanium, titanium alloys	> 1200 N/mm ²
H	S4.1 High-temperature super alloy Ni, Co and Fe-based	
	H1.1 Hardened steel/cast steel	45-55 HRC
	H1.2 Hardened steel/cast steel	55-64 HRC
	H1.3 Hardened steel/cast steel	64-70 HRC
H2	H2.1 Wear-resistant cast iron/chilled cast iron, GJN	
Sintered steel	e.g. SintD30	< 60 HRC
	e.g. SintD32	> 60 HRC

Surface finish requirement

- 1. Surface (R_z)
- 2. Scroll-free
- 3. Contact ratio

Cutting conditions	Machining length (land length)	Stock removal
1. Continuous cut ●	1. ≤ 45 mm	1. Finishing (ap ≤ 0.1 mm)
2. Interrupted cut ✎	2. ≤ 35 mm	
	3. ≤ 25 mm	
		2. Roughing and finishing (ap ≤ 0.3 mm)

3 Information on the tool (MAPAL tool design)			
Description of design, tool length, cutting material			
Design and cutting direction		Tool length (land length)	
Single holder, modular	Single holder, monolithic	45 mm	
			
Left	Right	Left	Right
Double holder, modular	Double holder, monolithic	45 mm	
			
Left	Right	Left	Right
PcBN insert * (The PcBN insert that is suitable is defined in accordance with the requirements on the part)			





VersaCut GROOVING AND TURNING SYSTEM

Introduction

Product overview	26
Designation key	28

VersaCut

Groove cutting	30
Standard holders	36

VersaCut

Maximum stability during hard grooving with PcBN

The flexible grooving system VersaCut from MAPAL offers the optimal prerequisites for the special requirements of hard machining. The PcBN-tipped inserts are clamped extremely stably. For this purpose a solid clamping plate presses the insert into a prismatic connection.

The clamping plate itself is embedded in the tool holder to ensure undisturbed chip flow and to protect the plate against wear. Due to the short projection length the inserts are very stable and can be changed quickly. Damage to the holder on insert fracture is excluded by the special insert design.

The system covers inserts of varying widths and shapes for recessing and groove turning, as well as for machining threads. Optionally PCD-tipped inserts or special designs are

possible. All inserts have the same connection shape and size so that only one holder size is necessary for grooving depths up to 5 mm and grooving widths from 1.2 to 6 mm. The holders are available with different shanks in a square design, with HSK-T or other modular systems, as well as in a large number of special designs.

The MAPAL VersaCut grooving system combines absolute stability and a broad variety of applications.

AT A GLANCE


- Optimal chip discharge due to embedded clamping plate, tool holder and leading edge on the insert with clearance
- Optionally with coolant outlet
- Maximum stability through the high clamping force, embedded clamping plate and prismatic mounting
- No damage to the grooving holder upon insert fracture



Tool features in detail



- 1 Holder
2 Threaded spindle

- 3 Clamping plate
4 Insert



Universal edge design T51

The chamfer prevents crater wear and burr formation depending on its specification. Other chamfer designs available on request.




Maximum stability during hard grooving with PcBN

- High clamping force
- Stable, embedded jaw
- Prismatic mounting



Application areas

Standardised inserts for grooving, groove turning and thread cutting



Designation key


MAPAL VersaCut

Groove cutting

VCI	C	I	-	EN	L	-	W400	00	T300
Series/type	Application			Design	Cutting width/diameter				Max. grooving depth
VCI	VersaCut Insert				L	Left design			
	EN Recessing insert, general				W400	Width 4.00 mm			
	SR Grooving insert for locking rings				D400	Diameter 4.00 mm (only for radius inserts)			
	SS Grooving insert for locking washers				P60	Thread profile 60°			
	SD Groove turning insert								
	GD Thread turning insert								
	AS Parting off insert								

Grooving holder with HSK-T shank

VCH	C	H	-	L	-	H	S	K	-	T	0	4	0	-	A	-	0	
Series/type	Design			Shank design	Shank size				Holder shape				Coolant supply					
VCH	VersaCut holder				L	Left design				HSK	HSK				0 °			
					R	Right design					T040 HSK-T40				Without IC			
											T063 HSK-T63				B 90 °			
															X Angle variable (e.g. X75 for 75°)			
															1 With IC			




Grooving holder with square shank and cylindrical shank

VCH	C	H	L	S	1	6	1	6	A	O	
VCH	VersaCut holder			Left design			Holder shape			Coolant supply	
	L	Right design			S	Square shank WxH [mm]			A	0 °	
	R				ZYL	Cylindrical shank Size [mm]			B	90 °	
									X	Angle variable (e.g. X75 for 75°)	
									0	Without IC	
									1	With IC	

VersaCut VCI-SD


Groove turning



W	T	R_E	Design	Specification	Order No.
$2 \pm 0,02$	4	0,2	Left	VCI-SDL-W200T400-R020T51-FU824	30316777
$2 \pm 0,02$	4	0,2	Right	VCI-SDR-W200T400-R020T51-FU824	30316783
$2 \pm 0,02$	4	0,4	Left	VCI-SDL-W200T400-R040T51-FU824	30316789
$2 \pm 0,02$	4	0,4	Right	VCI-SDR-W200T400-R040T51-FU824	30316797
$2,5 \pm 0,02$	4	0,2	Left	VCI-SDL-W250T400-R020T51-FU824	30316778
$2,5 \pm 0,02$	4	0,2	Right	VCI-SDR-W250T400-R020T51-FU824	30316784
$2,5 \pm 0,02$	4	0,4	Left	VCI-SDL-W250T400-R040T51-FU824	30316791
$2,5 \pm 0,02$	4	0,4	Right	VCI-SDR-W250T400-R040T51-FU824	30316798
$3 \pm 0,02$	5	0,2	Left	VCI-SDL-W300T500-R020T51-FU824	30316779
$3 \pm 0,02$	5	0,2	Right	VCI-SDR-W300T500-R020T51-FU824	30316785
$3 \pm 0,02$	5	0,4	Left	VCI-SDL-W300T500-R040T51-FU824	30316792
$3 \pm 0,02$	5	0,4	Right	VCI-SDR-W300T500-R040T51-FU824	30316799
$3,5 \pm 0,02$	5	0,2	Left	VCI-SDL-W350T500-R020T51-FU824	30316780
$3,5 \pm 0,02$	5	0,2	Right	VCI-SDR-W350T500-R020T51-FU824	30316786
$3,5 \pm 0,02$	5	0,4	Left	VCI-SDL-W350T500-R040T51-FU824	30316793
$3,5 \pm 0,02$	5	0,4	Right	VCI-SDR-W350T500-R040T51-FU824	30316800
$4 \pm 0,02$	5	0,2	Left	VCI-SDL-W400T500-R020T51-FU824	30316781
$4 \pm 0,02$	5	0,2	Right	VCI-SDR-W400T500-R020T51-FU824	30316787
$4 \pm 0,02$	5	0,4	Left	VCI-SDL-W400T500-R040T51-FU824	30316794
$4 \pm 0,02$	5	0,4	Right	VCI-SDR-W400T500-R040T51-FU824	30316801
$5 \pm 0,02$	5	0,2	Left	VCI-SDL-W500T500-R020T51-FU824	30316782
$5 \pm 0,02$	5	0,2	Right	VCI-SDR-W500T500-R020T51-FU824	30316788
$5 \pm 0,02$	5	0,4	Left	VCI-SDL-W500T500-R040T51-FU824	30316795
$5 \pm 0,02$	5	0,4	Right	VCI-SDR-W500T500-R040T51-FU824	30316802

VersaCut VCI-SD

Groove turning (radius insert)




View: Left design



W	T	R_E	Design	Specification	Order No.
$3 \pm 0,02$	5	1,5	Left	VCI-SDL-D300T500-R150T51-FU824	30316833
$3 \pm 0,02$	5	1,5	Right	VCI-SDR-D300T500-R150T51-FU824	30316828
$3,5 \pm 0,02$	5	1,75	Left	VCI-SDL-D350T500-R175T51-FU824	30316834
$3,5 \pm 0,02$	5	1,75	Right	VCI-SDR-D350T500-R175T51-FU824	30316829
$4 \pm 0,02$	5	2	Left	VCI-SDL-D400T500-R200T51-FU824	30316835
$4 \pm 0,02$	5	2	Right	VCI-SDR-D400T500-R200T51-FU824	30316830

VersaCut VCI-EN


Recessing insert



W	T	R _E	Design	Specification	Order No.
1,5 ±0,02	3,5	0,2	Left	VCI-ENL-W200T400-R020S59-FU824	30316736
1,5 ±0,02	3,5	0,2	Right	VCI-ENR-W150T350-R020T51-FU824	30316831
1,5 ±0,02	3,5	0,4	Left	VCI-ENL-W150T350-R040T51-FU824	30316857
1,5 ±0,02	3,5	0,4	Right	VCI-ENR-W150T350-R040T51-FU824	30316858
2 ±0,02	4	0,2	Left	VCI-ENL-W200T400-R020T51-FU824	30316694
2 ±0,02	4	0,2	Right	VCI-ENR-W200T400-R020T51-FU824	30316703
2 ±0,02	4	0,4	Left	VCI-ENL-W200T400-R040T51-FU824	30316710
2 ±0,02	4	0,4	Right	VCI-ENR-W200T400-R040T51-FU824	30316718
2,5 ±0,02	4	0,2	Left	VCI-ENL-W250T400-R020T51-FU824	30316696
2,5 ±0,02	4	0,2	Right	VCI-ENR-W250T400-R020T51-FU824	30316704
2,5 ±0,02	4	0,4	Left	VCI-ENL-W250T400-R040T51-FU824	30316711
2,5 ±0,02	4	0,4	Right	VCI-ENR-W250T400-R040T51-FU824	30316725
3 ±0,02	5	0,2	Left	VCI-ENL-W300T500-R020T51-FU824	30316697
3 ±0,02	5	0,2	Right	VCI-ENR-W300T500-R020T51-FU824	30316705
3 ±0,02	5	0,4	Left	VCI-ENL-W300T500-R040T51-FU824	30316712
3 ±0,02	5	0,4	Right	VCI-ENR-W300T500-R040T51-FU824	30316726
3,5 ±0,02	5	0,2	Left	VCI-ENL-W350T500-R020T51-FU824	30316699
3,5 ±0,02	5	0,2	Right	VCI-ENL-W350T500-R020T51-FU824	30316707
3,5 ±0,02	5	0,4	Left	VCI-ENL-W350T500-R040T51-FU824	30316715
3,5 ±0,02	5	0,4	Right	VCI-ENR-W350T500-R040T51-FU824	30316727
4 ±0,02	5	0,2	Left	VCI-ENL-W400T500-R020T51-FU824	30316700
4 ±0,02	5	0,2	Right	VCI-ENR-W400T500-R020T51-FU824	30316708
4 ±0,02	5	0,4	Left	VCI-ENL-W400T500-R040T51-FU824	30316716
4 ±0,02	5	0,4	Right	VCI-ENR-W400T500-R040T51-FU824	30316732
5 ±0,02	5	0,2	Left	VCI-ENL-W500T500-R020T51-FU824	30316702
5 ±0,02	5	0,2	Right	VCI-ENR-W500T500-R020T51-FU824	30316709
5 ±0,02	5	0,4	Left	VCI-ENL-W500T500-R040T51-FU824	30316717
5 ±0,02	5	0,4	Right	VCI-ENR-W500T500-R040T51-FU824	30316733

VersaCut VCI-SR, VCI-SS

Slots for locking rings, type SR



DIN 471		W	T	R _E	Design	Specification	Order No.
For shaft diameter	WNB						
18-26	1,3 H13	1,4 ±0,02	1,8	0,12	Left	VCI-SRL-W140T180-R012T51-FU824	30316679
18-26	1,3 H13	1,4 ±0,02	1,8	0,12	Right	VCI-SRR-W140T180-R012T51-FU824	30316673
28-35	1,6 H13	1,70 ±0,02	3	0,15	Left	VCI-SRL-W170T300-R015T51-FU824	30316680
28-35	1,6 H13	1,70 ±0,02	3	0,15	Right	VCI-SRR-W170T300-R015T51-FU824	30316674
36-48	1,85 H13	1,95 ±0,02	3	0,18	Left	VCI-SRL-W195T300-R018T51-FU824	30316681
36-48	1,85 H13	1,95 ±0,02	3	0,18	Right	VCI-SRR-W195T300-R018T51-FU824	30316675
50-63	2,15 H13	2,25 ±0,02	3	0,2	Left	VCI-SRL-W225T300-R020T51-FU824	30316682
50-63	2,15 H13	2,25 ±0,02	3	0,2	Right	VCI-SRR-W225T300-R020T51-FU824	30316677

Slots for locking washers, type SS



DIN 471		W	T	R _E	Design	Specification	Order No.
For shaft diameter	WNB						
10-14	1,15 +0,08	1,19 ±0,02	3	0,11	Left	VCI-SSL-W119T300-R011T51-FU824	30316688
10-14	1,15 +0,08	1,19 ±0,02	3	0,11	Right	VCI-SSR-W119T300-R011T51-FU824	30316683
11-15	1,25 +0,08	1,29 ±0,02	3	0,12	Left	VCI-SSL-W129T300-R012T51-FU824	30316689
11-15	1,25 +0,08	1,29 ±0,02	3	0,12	Right	VCI-SSR-W129T300-R012T51-FU824	30316684
13-18	1,35 +0,08	1,39 ±0,02	4	0,13	Left	VCI-SSL-W139T400-R013T51-FU824	30316692
13-18	1,35 +0,08	1,39 ±0,02	4	0,13	Right	VCI-SSR-W139T400-R013T51-FU824	30316685
16-24	1,55 +0,08	1,59 ±0,02	4	0,15	Left	VCI-SSL-W159T400-R015T51-FU824	30429005
16-24	1,55 +0,08	1,59 ±0,02	4	0,15	Right	VCI-SSR-W159T400-R015T51-FU824	30429004
20-31	1,8 +0,08	1,84 ±0,02	4	0,18	Left	VCI-SSL-W184T400-R018T51-FU824	30316693
20-31	1,8 +0,08	1,84 ±0,02	4	0,18	Right	VCI-SSR-W184T400-R018T51-FU824	30316686

Dimensions in mm.

VersaCut VCI-AS


Parting off



W	T	R _E	Design	Specification	Order No.
1,5 ±0,02	4,8	0,2	Left	VCI-ASL-W150T480-R020T51-FU824	30418274
1,5 ±0,02	4,8	0,2	Right	VCI-ASR-W150T480-R020T51-FU824	30419166
2 ±0,02	4,8	0,2	Left	VCI-ASL-W200T480-R020T51-FU824	30418276
2 ±0,02	4,8	0,2	Right	VCI-ASR-W200T480-R020T51-FU824	30419167
3 ±0,02	5	0,2	Left	VCI-ASL-W300T500-R020T51-FU824	30418277
3 ±0,02	5	0,2	Right	VCI-ASR-W300T500-R020T51-FU824	30419168

VersaCut VCI-GD

For metric 60° ISO thread




P	R _E	Design	Specification	Order No.
0,75	0,10	Left	VCI-GDL-P60T090-R010T51-FU824	30364781
0,75	0,10	Right	VCI-GDR-P60T090-R010T51-FU824	30316841
1,00	0,14	Left	VCI-GDL-P60T090-R014T51-FU824	30364783
1,00	0,14	Right	VCI-GDR-P60T090-R014T51-FU824	30316842
1,25	0,18	Left	VCI-GDL-P60T100-R018T51-FU824	30335855
1,25	0,18	Right	VCI-GDR-P60T100-R018T51-FU824	30316846
1,50	0,22	Left	VCI-GDL-P60T150-R022T51-FU824	30360047
1,50	0,22	Right	VCI-GDR-P60T150-R022T51-FU824	30316847
1,75	0,25	Left	VCI-GDL-P60T180-R025T51-FU824	30360050
1,75	0,25	Right	VCI-GDR-P60T180-R025T51-FU824	30316861
2,00	0,29	Left	VCI-GDL-P60T180-R029T51-FU824	30360053
2,00	0,29	Right	VCI-GDR-P60T180-R029T51-FU824	30316862
2,50	0,36	Left	VCI-GDL-P60T220-R036T51-FU824	30360056
2,50	0,36	Right	VCI-GDR-P60T220-R036T51-FU824	30316863
3,00	0,43	Left	VCI-GDL-P60T240-R043T51-FU824	30360058
3,00	0,43	Right	VCI-GDR-P60T240-R043T51-FU824	30316864

Designs for trapezoid thread (EU/USA), Whitworth thread are available on request.



VersaCut standard holder

HSK-T, short design, without gripper groove




View: Left design

Note:
Left holder requires left insert.
Right holder requires right insert.

Shank design	Size	l_1	l_2	Coolant supply	Holder shape	Design	Specification	Order No.
HSK-T	40-T	60	30	Without IC	0°	Left	VCH-L-HSK-T040-A-0	30519762
HSK-T	40-T	60	30	Without IC	0°	Right	VCH-R-HSK-T040-A-0	30519763
HSK-T	40-T	60	30	With IC	0°	Left	VCH-L-HSK-T040-A-1	30519765
HSK-T	40-T	60	30	With IC	0°	Right	VCH-R-HSK-T040-A-1	30519766
HSK-T	63-T	60	40	Without IC	0°	Left	VCH-L-HSK-T063-A-0	30519768
HSK-T	63-T	60	40	Without IC	0°	Right	VCH-R-HSK-T063-A-0	30519769
HSK-T	63-T	60	40	With IC	0°	Left	VCH-L-HSK-T063-A-1	30519772
HSK-T	63-T	60	40	With IC	0°	Right	VCH-R-HSK-T063-A-1	30519773

HSK-T, long design, with gripper groove



View: Left design

Note:
Left holder requires left insert.
Right holder requires right insert.


Shank design	Size	l_1	l_2	Coolant supply	Holder shape	Design	Specification	Order No.
HSK-T	40-T	100	30	Without IC	0°	Left	VCH-L-HSK-T040-A-0	30427900
HSK-T	40-T	100	30	Without IC	0°	Right	VCH-R-HSK-T040-A-0	30428073
HSK-T	40-T	100	30	With IC	0°	Left	VCH-L-HSK-T040-A-1	30428071
HSK-T	40-T	100	30	With IC	0°	Right	VCH-R-HSK-T040-A-1	30428072
HSK-T	63-T	100	40	Without IC	0°	Left	VCH-L-HSK-T063-A-0	30365905
HSK-T	63-T	100	40	Without IC	0°	Right	VCH-R-HSK-T063-A-0	30376187
HSK-T	63-T	100	40	With IC	0°	Left	VCH-L-HSK-T063-A-1	30320284
HSK-T	63-T	100	40	With IC	0°	Right	VCH-R-HSK-T063-A-1	30316478

Dimensions in mm.

Other shanks on request.


VersaCut standard holder

Square shank



Shank design	Size	l_1	l_2	l_3	l_4	Coolant supply	Holder shape	Design	Specification	Order No.
Square shank	12x12	150	49	12	19	Without IC	0°	Right	VCH-R-S1212-A-0	30774044
Square shank	12x12	150	49	12	19	Without IC	0°	Left	VCH-L-S1212-A-0	30774045
Square shank	16x16	150	49	16	23	With IC	0 °	Right	VCH-R-S1616-A-1	30663293
Square shank	16x16	150	49	16	23	With IC	0 °	Left	VCH-L-S1616-A-2	On request
Square shank	20x20	150	49	20	27	Without IC	0°	Left	VCH-L-S2020-A-0	30365899
Square shank	20x20	150	49	20	27	Without IC	0°	Right	VCH-R-S2020-A-0	30376199
Square shank	20x20	150	49	20	27	With IC	0°	Left	VCH-L-S2020-A-1	30320282
Square shank	20x20	150	49	20	27	With IC	0°	Right	VCH-R-S2020-A-1	30317676
Square shank	25x25	150	49	25	32	Without IC	0°	Left	VCH-L-S2525-A-0	30365901
Square shank	25x25	150	49	25	32	Without IC	0°	Right	VCH-R-S2525-A-0	30376202
Square shank	25x25	150	49	25	32	With IC	0°	Left	VCH-L-S2525-A-1	30320283
Square shank	25x25	150	49	25	32	With IC	0°	Right	VCH-R-S2525-A-1	30317677

Cylindrical shank




Shank design	Size	f	$d_1 \text{ min}$	l_1	l_2	Coolant supply	Holder shape	Design	Specification	Order No.
Cylindrical shank	25	16	31	150	23,5	With IC	90°	Left	VCH-L-ZYL025-B-1	30518232
Cylindrical shank	25	16	31	150	23,5	With IC	90°	Right	VCH-R-ZYL025-B-1	30419320

Spare parts for VersaCut standard holder

	Description	Design for	Order No.
	Clamping plate	Right holder	30321574
	Clamping plate	Left holder	30320414
	Threaded spindle	Right and left holder	10036727

Dimensions in mm.



EXTREMELY HARD CUTTING MATERIALS

PcBN and PCD-tipped indexable inserts





EXTREMELY HARD CUTTING MATERIALS

PcBN INDEXABLE INSERTS

Polycrystalline cubic boron nitride High performance, cost-effective, efficiency

Modern, stable machine tools with fast, powerful drives and high accuracies form the backbone of cost-effective manufacturing today. To be able to fully exploit the productivity potential of high cutting speeds and feeds also at the insert, it is appropriate to use modern, extremely hard cutting materials such as PcBN.

PcBN cutting materials from MAPAL create the ideal prerequisites for cost-effective machining due to their high hot hardness, wear resistance and edge strength. As a result, the machining times and as a consequence the

workpiece costs can be reduced significantly with very good part quality at the same time.

Compared to carbide, the productivity during the machining of cast iron and sintered iron materials can be increased significantly with PcBN cutting materials in the manufacturing process due to high machining values and long tool lives. During hard turning with PcBN, a significantly higher material removal rate is achieved compared to grinding. With the same part requirements, the productivity is generally higher and the machining costs lower. Machines for hard turning are in most

cases also cheaper to procure than grinding machines for comparable surface finishes. Hard turning can be undertaken dry. Grinding machines require grinding oils that gradually become soiled and that must be purified with a lot of effort, or they must be disposed of, or stored long-term.

ADVANTAGES

- PcBN grades for continuous cut and interrupted cuts
- Large selection of standard geometries and chamfer designs available for optimal tool life and quality
- Multiply tipped designs for greater cost-effectiveness of the tools
- Indexable inserts with high-accuracy G tolerance





PCD INDEXABLE INSERTS

Polycrystalline diamond Extremely hard and effective

On the usage of modern structural materials, whether in vehicle manufacture, in aerospace or also increasingly in mechanical engineering, the focus is on an improved energy balance. The energy consumption is to be lowered with the same or even better dynamic performance. For this reason the portion of non-ferrous metals, fibre-reinforced plastics (GFRP, CFRP) and sandwich materials is increasing continuously.

PCD is ideal as a cutting material for machining these workpiece materials. Due to its hardness and wear resistance even with

extremely abrasive materials, high cutting values and tool lives can be achieved. The cost-effectiveness of the machining is ensured in this manner. MAPAL started to rely on PCD during the design of high-performance tools at an early stage and has obtained broad know-how and many years of experience. Different machining tasks with varying requirements in relation to abrasiveness, part geometry and machines are realised with PCD.

To achieve optimal technology figures for the various requirement profiles and to fully exploit the performance of the PCD cutting material

and of the machines, an optimal cutting edge geometry must be manufactured with high accuracy and reproducible quality. Here MAPAL uses the latest machine technology for grinding and eroding the inserts. New technologies such as the laser machining of PCD are also used. Positive chip geometries and different chip breaker geometries are machined using lasers on the PCD indexable inserts that are used, for example, for long chipping types of aluminium. Short, easily removed chips are produced, which significantly increases the process reliability.




ADVANTAGES

- Highest cutting data and cost-effectiveness
- High accuracy of the cutting edge geometries
- Latest manufacturing methods offer additional possibilities

Designation key

For PcbN and PCD-tipped indexable inserts from MAPAL



Insert form

C	80 °
D	55 °
S	90 °
T	60 °
V	35 °
W	80 °
R	

Standard clearance angle

N	0 °
B	5 °
C	7 °
P	11 °

Tolerance

G	G class
---	---------

Fastening and/or chip breaker symbol, metric

Hole	Configuration	Chip breaker	Figure
W With	Cylindrical hole + countersink	No	
T With	Cylindrical hole + countersink on one side (40-60°)	One side	
B With	Cylindrical hole + countersink	No	
H With	Cylindrical hole + countersink on one side (70-90°)	One side	
A With	Cylindrical hole	No	
M With	Cylindrical hole	One side	
N Without	-	No	
X -	-	-	Spec. design

Insert thickness

	Thickness [mm]
01	1.59
02	2.38
03	3.18
T3	3.97
04	4.76
06	6.35


The thickness is measured from the contact surface on the indexable insert to the cutting edge.


Insert size

IC d [mm]	C	D	S	T	V	W	R	
5.56				09 (9.6)		03 (3.8)		02 0.2
6.0								04 0.4
6.35	06 (6.4)	07 (7.7)	06 (6.35)	11 (11.0)	11 (11.1)	04 (4.3)		08 0.8
7.94	08 (8.0)		07 (7.94)			05 (5.4)		
8.0							08	
9.525	09 (9.7)	11 (11.6)	09 (9.525)	16 (16.5)	16 (16.6)	06 (6.5)	09 (9.525)	12 1.2
10.0							10	
12.0							12	
12.7	12 (12.9)	15 (15.5)	12 (12.7)	22 (22.0)		08 (8.7)	12 (12.7)	

Corner radius

		Cutting material	Cutting material
PCD grade		PU620	FP823 (coated)
PcBN grade		PU660	FP834 (coated)
PcBN grade		PU670	FP853 (coated)
PcBN grade			FU430
PcBN grade			FU720
PcBN grade			FU824
PcBN grade			FU872
O A B - F P 8 5 3 - R			
Cutting direction		Tipping	Can be reground
N Neutral		S Solid	R Can be reground
X Right/left		F Full face on one side	
L Left		E Full face on both sides	
R Right		A Tipped on one side, one corner or full length	
Chip breaker		B Tipped on one side, two corners	
Tipping		C Tipped on one side, three corners	
Can be reground		K Tipped on one side, one corner	
Can be reground		L Tipped on both sides, two corners	
Can be reground		M Tipped on both sides, three corners	
Can be reground		N Tipped on both sides, four corners	
Cutting edge design			
F Sharp edged			
E Rounded			
T Chamfered			
S Chamfered and rounded			
W Wiper			





PcBN-TIPPED INDEXABLE INSERTS

Introduction


Selection procedure	46
Cutting material overview with application examples	50
Product overview PcBN-tipped indexable inserts	52

PcBN-tipped indexable inserts

Product range	54
---------------	----

Selection procedure for PcbN indexable inserts (1/2)

The simple way to the right insert based on the example of a CNGA indexable insert.



External machining

1.1 Recommendation for indexable insert shape and clearance angle

Insert form	Face machining	Longitudinal turning face turning	Profile turning	Clearance angle	
				Machining diameter:	
	80 °	★	★	Positive $\varnothing < 15$ mm	
				Negative $\varnothing > 15$ mm	
	55 °	■	■	★**	Positive $\varnothing < 15$ mm Negative $\varnothing > 15$ mm
					 
	90 °	■			Positive $\varnothing < 15$ mm Negative $\varnothing > 15$ mm
					 
	60 °	■	■	■	Positive $\varnothing < 15$ mm Negative $\varnothing > 15$ mm
					 
	35 °			■	Positive $\varnothing < 15$ mm Negative $\varnothing > 15$ mm
					 –
		■		■	Positive $\varnothing < 15$ mm Negative $\varnothing > 15$ mm
					 –
	80 °	■	■		Positive $\varnothing < 15$ mm Negative $\varnothing > 15$ mm
					 –

★ First choice ■ Suitable ■ Suitable in some situations

* Preferred clearance angle ** Pay attention to plunge angle

2.1 Recommendation for corner radius

Depending on the part contour required or requirements from part drawing

Cutting pressure drops	General machining 1st choice ★★★	Cutting pressure increases
Negative indexable insert R 0.4	R 0.8	R 1.2
Positive indexable insert R 0.2	R 0.4	R 0.8
- Machining thin-walled parts - Reduced tendency to vibration - Better circularity	- More stable insert with interrupted cuts - Better surface with same feed	

3

Cutting edge design depending on the cutting material

Cutting edge design

S 1 4

Page 48
(see 3.0)

Cutting direction

N

-

Chip groove

O A

Tipping

B

-

Constant neutral cutting direction (universal)

Continuous without chip groove

For selection see pages with tables

3

Cutting material types
Selection limited by workpiece material and cutting conditions

PcBN grades

F P 8 5 3

Page 48
(see 3.0)

Internal machining

1.2 Recommendation for indexable insert form and clearance angle

Insert form	Longitudinal turning	Face machining	Profile turning	Clearance angle	Machining diameter: $\varnothing > 35 \text{ mm}$ = negative indexable insert $\varnothing < 35 \text{ mm}$ = positive indexable insert	
C 80 °	★	★		Negative $\varnothing > 35 \text{ mm}$		CN
				Positive $\varnothing < 35 \text{ mm}$		CC*/CP
D 55 °	■	■	★**	Negative $\varnothing > 35 \text{ mm}$		DN
				Positive $\varnothing < 35 \text{ mm}$		DC*/DP
S 90 °	■			Negative $\varnothing > 35 \text{ mm}$		SN
				Positive $\varnothing < 35 \text{ mm}$		SC
A 60 °	■	■	■	Negative $\varnothing > 35 \text{ mm}$		TN
				Positive $\varnothing < 35 \text{ mm}$		TC*/TP
V 35 °			■	Negative $\varnothing > 35 \text{ mm}$		-
				Positive $\varnothing < 35 \text{ mm}$		VB/VC
R	■			Negative $\varnothing > 35 \text{ mm}$		RN
				Positive $\varnothing < 35 \text{ mm}$		-
W 80 °		■	■	Negative $\varnothing > 35 \text{ mm}$		WN
				Positive $\varnothing < 35 \text{ mm}$		-

★ First choice ■ Suitable □ Suitable in some situations

* Preferred clearance angle ** Pay attention to plunge angle

2.2 Recommendation for corner radius

Depending on the part contour required or requirements from part drawing

Cutting pressure drops

General machining 1st choice
★★★

Cutting pressure increases

Negative indexable insert
R 0.2 R 0.4 R 0.8

Positive indexable insert
R 0.4 R 0.8 R 1.2

- Machining thin-walled parts
- Reduced tendency to vibration
- Better circularity

- More stable insert with interrupted cuts
- Better surface with same feed

Selection procedure for PcbN indexable inserts (2/2)

Definition of the PcbN grade and the cutting edge design based on the example of a CNGA indexable insert.

Selection page 46/47.

C N G A 1 2 0 4 0 4

3 Cutting edge design dependent on the cutting material selected

S 1 4

N - 0 A

B -


3 Cutting material types Selection limited by workpiece material and cutting conditions

F P 8 5 3

3.0 Selection of the PcbN cutting material grade and the cutting edge design

Cutting material *			FP823	FP834	FP853	FU430		FU720		FU824		FU872
Machining			General turning	General turning	General turning	Finish turning		Finish turning		Grooving	Chasing	Rough turning
Cutting edge design			T13	S14	S12	E01	T51	E01	T51	T51	T51	S09
Cutting conditions			● ●	●	●	●	●	●	●	●	●	●
K	K1	K1.1	Cast iron with lamellar graphite (grey cast iron), GJL	< 300 N/mm ²			★	★	■	■		★
	K2	K2.1	Cast iron with spheroidal graphite, GJS	< 500 N/mm ²		■	★	★	■	■		
	K2	K2.2	Cast iron with spheroidal graphite, GJS	500-800 N/mm ²	■	★						
	K2	K2.3	Cast iron with spheroidal graphite, GJS	> 800 N/mm ²	★	■						
S	S2	S2.1	Titanium, titanium alloys	< 1200 N/mm ²	■		■	■				
	S2	S2.2	Titanium, titanium alloys	> 1200 N/mm ²	■		■	■				
S4	S4	S4.1	High-temperature super alloy Ni, Co and Fe-based		■		★	★				
H	H1	H1.1	Hardened steel/cast steel	52-58 HRC	★ ■ ★ ■ ★					★	★	
	H1	H1.2	Hardened steel/cast steel	58-63 HRC	★ ■ ★ ■ ★					★	★	
	H1	H1.3	Hardened steel/cast steel	> 63 HRC	■	★				★	★	
H2	H2	H2.1	Wear-resistant cast iron/chilled cast iron, GJN				★	★	■	■		
Sintered steel			e.g. SintD30	< 60 HRC	★							
Sintered steel			e.g. SintD32	> 60 HRC			★	★				

★ First choice ■ Alternative




Overview of cutting edge design

Along with the PcbN grade and the cutting parameters used, the selection of suitable cutting edge designs is the biggest variable to have a positive impact on the machining result produced by the indexable insert. Longer tool lives, better surface quality or increased dimensional accuracy on the part are in many cases dependent on the chamfer geometry selected.

T


Chamfered cutting edge (T)

A chamfered cutting edge is the preferred design for a continuous to slightly interrupted cut. The chamfer prevents crater wear and burr formation depending on its characteristic.

**S**

Chamfered and rounded cutting edge (S)


Rounding of the chamfered cutting edge lends the insert additional stability. This design is particularly suitable for high loads with continuous and interrupted cut.

**F**

Sharp edged cutting edge (F)

Sharp edged and rounded cutting edge (E)




Sharp edged cutting edges transmit only low compressive forces on the part to be machined and are particularly suitable for thin-walled parts. Rounding lends additional stability.

**W**

Wiper (W)

In comparison to a conventional turning insert, with the wiper geometry an R_a value several times better is achieved with the same feed.

If the same R_a value is to be achieved as with a standard turning insert, at least double the feed can be used with the turning insert with wiper geometry.



2 to 4-times higher feed = same surface finish
Same feed = 2 to 4-times better surface finish


(Part and machine stability are prerequisites)


Note: Pay attention to tool setting angle!

C insert 95°









D insert 93° (double-sided wiper function only possible during diameter machining)

Overview of PcBN cutting materials with application examples

FP823	Application example: GEARWHEEL (face and internal turning, continuous cut)	
<p>This coating grade covers a large spectrum of applications and can be used for continuous cut and interrupted cut, preferably with hardened steel and with dry machining. The PcBN substrate has high cutting edge stability.</p>		<p>Stock removal a_p: 0.2 mm Cutting speed v_c: 140 m/min Feed f: 0.11 mm Material: Sint D32 Density: 6.8-7.2 Cooling: Air</p> <p>Indexable insert: CCGW09T308S56N-0AB-FP823</p> 
FP834	Application example: CROWN WHEEL (face turning, interrupted cut)	 <p>Stock removal a_p: 0.15 mm Cutting speed v_c: 150 m/min Feed f: 0.28 mm Material: 20MnCr5 Hardness: 60 ± 2 HRC Cooling: Air</p> <p>Indexable insert: RNGN090300S60N-0AF-FP834</p> 
FP853	Application example: DRIVE SHAFT (longitudinal turning, continuous cut)	 <p>Stock removal a_p: 0.15 mm Cutting speed v_c: 180 m/min Feed f: 0.07 mm Material: 16MnCr5 Hardness: 60 ± 2 HRC Cooling: Air</p> <p>Indexable insert: DNGA150608T15N-0AB-FP853</p> 

FU430 / FU720	Application example: CYLINDER SLEEVE (finishing using FU430)
<p>These PcbN grades with high CBN content feature very high wear resistance with good ductility characteristics. They are used for machining cast materials, super alloys on sintered steels. The cutting material FU720 was developed especially for machining stellites.</p>	 <p>Stock removal a_p: 0.25 mm Cutting speed v_c: 780 m/min Feed f: 0.075 mm Number of cutting edges: z=2 Diameter: 69 mm Length: 132 mm Cooling: Emulsion</p> <p>Indexable insert: SNGN090304T13N-0AE-FU430</p> 
FU824	Application example: THREAD PLUG GAUGE (23 cuts per part)
<p>Universal grade especially for grooving and groove turning. Can be used for both continuous cut and interrupted cut.</p>	 <p>Material removal: 0.04 mm Cutting speed v_c: 100 m/min Pitch: 1.5 Material: 100Cr6 Hardness: 62 HRC Cooling: Air</p> <p>Indexable insert: VCI-GDL-P60T150-R022T51-FU824</p> 
FU872	Application example: BRAKE DRUM
<p>Wear-resistant PcbN grade with high CBN content ideal for roughing grey cast iron (GG) in conjunction with emulsion cooling.</p>	 <p>Stock removal a_p: 4-5 mm Cutting speed v_c: 1300 m/min Feed f: 0.6 mm Material: GG25 (GJL250) Cooling: Emulsion</p> <p>Indexable insert: SNGN120416S09N-0AS-FU872</p> 

Product overview PcBN indexable inserts

Insert form	CCGW, double	CNGA, double	CNGA, quadruple	CNGN, sandwich
C 				
Page	54	54	55	55
Insert form	DCGW, double	DNGA, double	DNGA, quadruple	
D 				
Page	56	56	57	
Insert form	SCGW, single	SNGA, eightfold	SNGN, sandwich	SNGN, solid
S 				
Page	57	58	58	58
Insert form	TCGW, single	TCGW, triple	TNGA, triple	TNGA, sixfold
T 				
Page	59	60	60	61
Insert form	VBGW, double	VCGW, double	VNGA, quadruple	
V 				
Page	62	63	63	
Insert form	WNGA, sixfold			
W 				
Page	64			
Insert form	RNGN, sandwich	RNGN, solid		
R 				
Page	64	64		

CNGN, solid



55

SPGN, full face



59

TNGN, sandwich




61

TNGN, solid



61



TPGW, single



62

CCGW



PcBN indexable insert, double



Specification	Dimensions				FP834		FP823		FP853		FU430		
	d	s	r	d ₁	S14	T13	W85	S12	W85	E01	T51	W79	
CCGW 060202 ...N-0AB	6,35	2,38	0,2	2,8	30795326	30250322		30463141		30233102	30233104		
CCGW 060204 ...N-0AB	6,35	2,38	0,4	2,8	30795330	30248120		30260631		30233116	30233118		
CCGW 09T302 ...N-0AB	9,52	3,97	0,2	4,4	30795332	30325411		30463142		30503842	30324916		
CCGW 09T304 ...N-0AB	9,52	3,97	0,4	4,4	30293783	30236943	30254227	30436023	30463147	30233222	30233224	30233225	
CCGW 09T308 ...N-0AB	9,52	3,97	0,8	4,4	30269636	30243314	30483993	30277360	30463148	30233236	30233238	30233239	

CNGA


PcBN indexable insert, double



Specification	Dimensions				FP834		FP823		FP853		FU430		
	d	s	r	d ₁	S14	W87	T13	W87	S12	W87	E01	T51	W82
CNGA 120404 ...N-0AB	12,7	4,76	0,4	5,13	30329409	30795335	30463024	30463027	30463159	30463164	30463042	30463045	30463051
CNGA 120408 ...N-0AB	12,7	4,76	0,8	5,13	30494263	30795338	30463025	30463028	30463160	30285685	30463043	30463046	30463052
CNGA 120412 ...N-0AB	12,7	4,76	1,2	5,13	30272654	30416606	30463026	30463029	30463161	30463165	30463044	30463047	30463053

CNGA


PcBN indexable insert, quadruple



Specification	Dimensions				FP834		FP823		FP853		FU430			
	d	s	r	d ₁	S14	W87	T13	W87	S12	W87	W82	T51	W82	
CNGA 120404 ...N-OAL	12,7	4,76	0,4	5,13	30469907	30795442	30262853	30262892	30463166	30463172	30262857	30262858	30262894	
CNGA 120408 ...N-OAL	12,7	4,76	0,8	5,13	30371652	30471007	30243344	30262897	30463167	30463173	30262872	30262873	30262899	
CNGA 120412 ...N-OAL	12,7	4,76	1,2	5,13	30292848	30795443	30262883	30262902	30463168	30463174	30262887	30262888	30262904	

CNGN

PcBN indexable insert




Specification	Dimensions			FU720			FU430			FU872	S09
	d	s	r	E01	T51	W87	E01	T51	E01		
CNGN 090304...N-OAE	9,52	3,18	0,4	30263431	30263432		30263440	30263441			
CNGN 090308...N-OAE	9,52	3,18	0,8	30263434	30263435		30263443	30263444			
CNGN 090312...N-OAE	9,52	3,18	1,2	30263437	30263438		30263446	30263447			
CNGN 120408...N-OAE	12,7	4,76	0,8	30262905	30262906	30262917	30262908	30262909	30262918		
CNGN 120412...N-OAE	12,7	4,76	1,2	30262911	30262912	30262919	30262914	30262915	30262920		
CNGN 120408...N-OAS	12,7	4,76	0,8							30795450	
CNGN 120412...N-OAS	12,7	4,76	1,2							30796222	

Dimensions in mm.

DCGW


PcBN indexable insert, double



Specification	Dimensions				FP834	FP823	FP853	FU430							
	d	s	r	d ₁				S14	T13	W87	S12	W85	E01	T51	W79
DCGW 070202 ...N-0AB	6,35	2,38	0,2	2,8	30439405	30262935		30381164			30233342	30233344			
DCGW 070204 ...N-0AB	6,35	2,38	0,4	2,8	30439407	30251470		30260629			30233372	30233374			
DCGW 070208 ...N-0AB	6,35	2,38	0,8	2,8	30795399	30262947		30463175			30262948	30262949			
DCGW 11T302 ...N-0AB	9,535	3,97	0,2	4,4	30814344	30262960		30414615			30262964	30262965			
DCGW 11T304 ...N-0AB	9,535	3,97	0,4	4,4	30403895	30262969	30262973	30403893	30463181	30233402	30233404	30233405			
DCGW 11T308 ...N-0AB	9,535	3,97	0,8	4,4	30360012	30243312	30262974	30428478	30463182	30233432	30233434	30233435			

DNGA

PcBN indexable insert, double




Specification	Dimensions				FP834	FP823	FP853	FU430							
	d	s	r	d ₁				S14	T13	W87	S12	W87	E01	T51	W82
DNGA 150404 ...N-0AB	12,7	4,76	0,4	5,13	30795400	30463087	30463093	30463183	30463190	30463119	30463125	30463137			
DNGA 150408 ...N-0AB	12,7	4,76	0,8	5,13	30795401	30463088	30463094	30463184	30463191	30463120	30463126	30463138			
DNGA 150412 ...N-0AB	12,7	4,76	1,2	5,13	30795405	30463089		30463185		30463121	30463127				
DNGA 150604 ...N-0AB	12,7	6,35	0,4	5,13	30329407	30463090	30463095	30483983	30463192	30463122	30463128	30463139			
DNGA 150608 ...N-0AB	12,7	6,35	0,8	5,13	30293187	30463091	30483987	30483984	30463193	30463123	30463129	30463140			
DNGA 150612 ...N-0AB	12,7	6,35	1,2	5,13	30310609	30463092		30483985		30463124	30463130				

Dimensions in mm.

DNGA


PcBN indexable insert, quadruple



Specification	Dimensions				FP834	FP823	FP853	FU430		
	d	s	r	d ₁				S14	T13	
DNGA 150404 ...N-OAL	12,7	4,76	0,4	5,13	30795438	30463489				
DNGA 150408 ...N-OAL	12,7	4,76	0,8	5,13	30795439	30463492		30463502	30463503	
DNGA 150412 ...N-OAL	12,7	4,76	1,2	5,13	30795441	30483988		30463505	30463506	
DNGA 150604 ...N-OAL	12,7	6,35	0,4	5,13	30419250	30264690	30463194	30264694	30264695	
DNGA 150608 ...N-OAL	12,7	6,35	0,8	5,13	30419247	30264704	30463195	30264708	30264709	
DNGA 150612 ...N-OAL	12,7	6,35	1,2	5,13	30425244	30264718	30463196	30264722	30264723	

SCGW

PcBN indexable inserts, single




Specification	Dimensions				FP823	FU720		FU430		
	d	s	r	d ₁		T13	E01	T51	E01	
SCGW 09T304 ...N-OAA	9,52	3,97	0,4	4,4	30463510	10106276	10106278	10106283	10106285	
SCGW 09T308 ...N-OAA	9,52	3,97	0,8	4,4	30463513	10106290	10106292	10106297	10106299	

Dimensions in mm.

SNGA


PcBN indexable insert, eightfold



Specification	Dimensions				FP823	FU430	
	d	s	r	d ₁			
SNGA 120404 ...N-OAN	12,7	4,76	0,4	5,13	30263055	30263059	30263060
SNGA 120408 ...N-OAN	12,7	4,76	0,8	5,13	30263070	30263074	30263075
SNGA 120412 ...N-OAN	12,7	4,76	1,2	5,13	30263085	30263089	30263090

SNGN


PcBN indexable insert



Specification	Dimensions			FU720		FU430		FU872	
	d	s	r	E01	T13	E01	T51	S09	
SNGN 090308 ...N-OAE	9,52	3,18	0,8	30263092	30263094	30263095	30263096		
SNGN 090312 ...N-OAE	9,52	3,18	1,2	30263098	30263100	30263101	30263102		
SNGN 120408 ...N-OAE	12,7	4,76	0,8	30263104	30263106	30263107	30263108		
SNGN 120412 ...N-OAE	12,7	4,76	1,2	30263540	30263112	30263541	30263114		
SNGN 090308 ...N-OAS	9,52	3,18	0,8					30796235	
SNGN 090312 ...N-OAS	9,52	3,18	1,2					30796236	
SNGN 120408 ...N-OAS	12,7	4,76	0,8					30796245	
SNGN 120412 ...N-OAS	12,7	4,76	1,2					30796249	

SPGN


PcBN indexable insert, full face



Specification	Dimensions			FU720		FU430		
	d	s	r	E01	T51	E01	T51	
SPGN 090308 ...N-0AF	9,52	3,18	0,8	30263026	30263027	30263029	30263030	
SPGN 090312 ...N-0AF	9,52	3,18	1,2	30263032	30263033	30263035	30263036	

TCGW

PcBN indexable inserts, single




Specification	Dimensions				FP823		FU430		
	d	s	r	d ₁	T13	E01	T51		
TCGW 090204...N-0AA	5,56	2,38	0,4	2,5	30463516	10106452	10106454		
TCGW 090208...N-0AA	5,56	2,38	0,8	2,5	30463519	10106464	10106466		
TCGW 110204...N-0AA	6,35	2,38	0,4	2,8	30463522	30227878	30227880		
TCGW 110208...N-0AA	5,56	2,38	0,8	2,5	30463525	30227890	30227892		

Dimensions in mm.

TCGW


PcBN indexable insert, triple



Specification	Dimensions				FP834	FP823	FU430		
	d	s	r	d ₁			S14	T13	
TCGW 090204...N-OAC	5,56	2,38	0,4	2,5	30796344	30463528	30463538	30324959	
TCGW 090208...N-OAC	5,56	2,38	0,8	2,5	30796348	30463531	30463541	30324961	
TCGW 110204...N-OAC	6,35	2,38	0,4	2,8	30478684	30463534	30463544	30324962	
TCGW 110208...N-OAC	5,56	2,38	0,8	2,5	30478690	30463537	30463547	30324964	

TNGA


PcBN indexable insert, triple



Specification	Dimensions			FP834	FP823	FP853	FU430		
	d	s	r				S14	T13	
TNGA 160404 ...N-OAC	9,52	4,76	0,4	30796351	30263118	30463214	10106608	10106610	
TNGA 160408 ...N-OAC	9,52	4,76	0,8	30478691	30263121	30463215	10106620	10106622	
TNGA 160412 ...N-OAC	9,52	4,76	1,2	30372232	30263124	30463216	10106632	10106634	

TNGA


PcBN indexable insert, sixfold



Specification	Dimensions				FP834	FP823	FP853	FU430		
	d	s	r	d ₁				S14	T13	
TNGA 160404 ...N-OAM	9,52	4,76	0,4	3,81	30796364	30263133	30796374	30263137	30263138	
TNGA 160408 ...N-OAM	9,52	4,76	0,8	3,81	30796366	30263148	30365948	30263152	30263153	
TNGA 160412 ...N-OAM	9,52	4,76	1,2	3,81	30796370	30263163	30366010	30263167	30263168	

TNGN

PcBN indexable insert




Specification	Dimensions			FU720		FU430		FP823	FP872	
	d	s	r	E01	T51	E01	T51			
TNGN 110304 ...N-OAE	6,35	3,18	0,4	30263476	30263477	30263485	30263486	30263467		
TNGN 110308 ...N-OAE	6,35	3,18	0,8	30263479	30263480	30263488	30263489	30263470		
TNGN 110312 ...N-OAE	6,35	3,18	1,2	30263482	30263483	30263491	30263492	30263473		
TNGN 110304 ...N-OAS	6,35	3,18	0,4						30796254	
TNGN 110308 ...N-OAS	6,35	3,18	0,8						30796257	
TNGN 110312 ...N-OAS	6,35	3,18	1,2						30796263	

Dimensions in mm.

TPGW


PcBN indexable inserts, single



Specification	Dimensions				FP823	FU430	
	d	s	r	d ₁			
TGKW 090204...N-0AA	5,56	2,38	0,4	2,5	30463564	10106556	10106558
TGKW 090208...N-0AA	5,56	2,38	0,8	2,5	30463567	10106568	10106570
TGKW 110204...N-0AA	6,35	2,38	0,4	2,8	30463570	30240075	30240076
TGKW 110208...N-0AA	6,35	2,38	0,8	2,8	30463573	30240087	30240088

VBGW


PcBN indexable insert, double



Specification	Dimensions				FP834	FP823	FP853	FU430		
	d	s	r	d ₁						
VBGW 160404 ...N-0AB	9,52	4,76	0,4	4,4	30572248	30263190	30463231	30463237	30263194	30263195
VBGW 160408 ...N-0AB	9,52	4,76	0,8	4,4	30795407	30252534	30463232	30463238	30263209	30263210
VBGW 160412 ...N-0AB	9,52	4,76	1,2	4,4	30795414	30263220	30463233	30463239	30263224	30263225

VCGW


PcBN indexable insert, double



Specification	Dimensions				FP834	FP823	FP853	FU430		
	d	s	r	d ₁				E01	T51	
VCGW 110302 ...N-0AB	6,35	3,18	0,2	2,9	30795415	30263247	30463240	30263251	30263252	
VCGW 110304 ...N-0AB	6,35	3,18	0,4	2,9	30580485	30263262	30463241	30263266	30263267	
VCGW 160404 ...N-0AB	9,52	4,76	0,4	4,4	30795417	30263277	30463242	30263281	30263282	
VCGW 160408 ...N-0AB	9,52	4,76	0,8	4,4	30795420	30263292	30463243	30263296	30263297	
VCGW 160412 ...N-0AB	9,52	4,76	1,2	4,4	30795422	30263307	30463244	30263311	30263312	

VNGA

PcBN indexable insert, quadruple




Specification	Dimensions				FP823	FU430		
	d	s	r	d ₁		T13	E01	
VNGA 160404 ...N-0AL	9,52	4,76	0,2	3,81	30263322	30263326	30263327	
VNGA 160408 ...N-0AL	9,52	4,76	0,4	3,81	30263337	30263341	30263342	
VNGA 160412 ...N-0AL	9,52	4,76	0,8	3,81	30263352	30263356	30263357	

Dimensions in mm.

WNGA


PcBN indexable insert, sixfold



Specification	Dimensions				FP823	
	d	s	r	l ₁		
WNGA 080404 ...N-OAM	12,7	4,76	0,4	5,13	30263394	
WNGA 080408 ...N-OAM	12,7	4,76	0,8	5,13	30263409	
WNGA 080412 ...N-OAM	12,7	4,76	1,2	5,13	30263424	

RNGN

PcBN indexable insert



0AE = sandwich

0AS = solid

Specification	Dimensions		FU720		FU430		FP823	FU872	
	d	s	E01	T51	E01	T51			
RNGN 060300 ...N-0AS	6,35	3,18					30263373		
RNGN 090300 ...N-OAE	9,52	3,18	10106842	10106844	10106849	10106851	30243780		
RNGN 120400 ...N-OAE	12,7	4,76	30263359	30263360	30263362	30263363			
RNGN 090300 ...N-0AS	9,52	3,18					30796268		
RNGN 120400 ...N-0AS	12,7	4,76					30796273		





PCD-TIPPED INDEXABLE INSERTS

Introduction


Selection procedure	68
Product overview PCD-tipped indexable inserts	72

PCD-tipped indexable inserts

Product range	74
---------------	----

Selection procedure for PCD indexable inserts (1/2)

The simple way to the right insert based on the example of a CCGT indexable insert.



External machining

1.1 Recommendation for indexable insert shape and clearance angle

Insert form	Face machining	Longitudinal turning face turning	Profile turning	Clearance angle	
				Machining diameter:	
	80 °	★	★	Positive $\varnothing < 15$ mm	
				Negative $\varnothing > 15$ mm	
	55 °	■	■	★**	Positive $\varnothing < 15$ mm Negative $\varnothing > 15$ mm
					 
	90 °	■			Positive $\varnothing < 15$ mm Negative $\varnothing > 15$ mm
					 
	60 °	■	■	■	Positive $\varnothing < 15$ mm Negative $\varnothing > 15$ mm
					 
	35 °			■	Positive $\varnothing < 15$ mm Negative $\varnothing > 15$ mm
					 –
		■		■	Positive $\varnothing < 15$ mm Negative $\varnothing > 15$ mm
					 –
	80 °	■	■		Positive $\varnothing < 15$ mm Negative $\varnothing > 15$ mm
					 –

★ First choice ■ Suitable ■ Suitable in some situations

* Preferred clearance angle ** Pay attention to plunge angle

2.1 Recommendation for corner radius

Depending on the part contour required or requirements from part drawing

Cutting pressure drops	General machining 1st choice ★★★	Cutting pressure increases
Negative indexable insert R 0.4	R 0.8	R 1.2
Positive indexable insert R 0.2	R 0.4	R 0.8
- Machining thin-walled parts - Reduced tendency to vibration - Better circularity	- More stable insert with interrupted cuts - Better surface with same feed	

Cutting edge design

F **O** **1**Continuously
sharp edged

Cutting direction

NConstant neutral
cutting direction
(universal)

-

3

Cutting material types
Selection limited by workpiece
material and cutting conditions

Chip groove

C **1**Depending on
cutting material
grade

Tipping

AContinuous corner or
tipped along full length

PcBN grades

P **U** **6** **6** **0**Page 70/71
(see 3.0)

Internal machining

1.2 Recommendation for indexable insert form and clearance angle

Insert form	Longitudinal turning	Face machining	Profile turning	Clearance angle	Machining diameter: $\varnothing > 35 \text{ mm}$ = negative indexable insert $\varnothing < 35 \text{ mm}$ = positive indexable insert		
	80 °	★	★		Negative $\varnothing > 35 \text{ mm}$		CN
					Positive $\varnothing < 35 \text{ mm}$		CC*/CP
	55 °	■	■	★**	Negative $\varnothing > 35 \text{ mm}$		DN
					Positive $\varnothing < 35 \text{ mm}$		DC*/DP
	90 °	■			Negative $\varnothing > 35 \text{ mm}$		SN
					Positive $\varnothing < 35 \text{ mm}$		SC
	60 °	■	■	■	Negative $\varnothing > 35 \text{ mm}$		TN
					Positive $\varnothing < 35 \text{ mm}$		TC*/TP
	35 °			■	Negative $\varnothing > 35 \text{ mm}$		-
					Positive $\varnothing < 35 \text{ mm}$		VB/VC
		■			Negative $\varnothing > 35 \text{ mm}$		RN
					Positive $\varnothing < 35 \text{ mm}$		-
	80 °		■	■	Negative $\varnothing > 35 \text{ mm}$		WN
					Positive $\varnothing < 35 \text{ mm}$		-

★ First choice ■ Suitable □ Suitable in some situations

* Preferred clearance angle ** Pay attention to plunge angle

2.2 Recommendation for corner radius


Depending on the part contour required
or requirements from part drawingCutting pressure
dropsGeneral
machining
1st choice
★★★Cutting pressure
increasesNegative indexable insert
R 0.2 R 0.4 R 0.8Positive indexable insert
R 0.4 R 0.8 R 1.2

- Machining thin-walled parts
- Reduced tendency to vibration
- Better circularity

- More stable insert with interrupted cuts
- Better surface with same feed

Selection procedure for PCD indexable inserts (2/2)

Definition of the PCD grade and the cutting edge design based on the example of a CCGT indexable insert.



3 Cutting material types
Selection limited by workpiece material and cutting conditions

3.0 Selection of the PCD cutting material grade and the cutting edge design F01



		Cutting material	PU 620		PU660 with C1		PU670 with C2				
		Cutting conditions	●	●	☒	●	●	☒	●	●	☒
Machining group	Material	Strength/hardness									
N	N1.1	Aluminium, non-alloy and alloy < 3 % Si				★	★		■	■	★
	N1.2	Aluminium, alloy ≤ 7 % Si				★	★		■	■	★
	N1.3	Aluminium, alloy > 7-12 % Si	★	★					■	■	★
	N1.4	Aluminium, alloy > 12 % Si	★	★							★
	N2.1	Copper, non-alloy and low-alloy	< 300 N/mm ²	★	★				■	■	★
	N2.2	Copper, alloy	> 300 N/mm ²	★	★	★			■	■	■
	N2.3	Brass, bronze, gunmetal	< 1200 N/mm ²	★	★	★					
	N3.1	Graphite		★	★	★					
	N4.1	Plastic, thermoplastics		★	★	★					
	N4.2	Plastic, thermosets		★	★	★					
	N4.3	Plastic, foams		★	★	★					

★ First choice ■ Alternative

PCD cutting material PU620

PU620	Application example: ALLOY WHEEL	
Universal, fine grain PCD grade for the efficient machining of non-ferrous metals as well as non-metallic workpiece materials such as fibre-reinforced plastics. It is characterised in particular by high edge stability with good wear resistance and high quality surface finish.		Stock removal ap: 0.2 mm Spindle speed: 1,500 rev/min Feed f: 0.16 mm Number of cutting edges: 1 Diameter: 19 inch Material: AISi7 Cooling: MQL Indexable insert: VPGW220518

Rake angle geometry for cutting material PU620



Example	Geometry	Application description
	0° rake angle	Medium cutting pressure <ul style="list-style-type: none"> - Solid or particularly stable parts - Tight tolerances - High quality surface finish
	Positive rake angle	Low cutting pressure <ul style="list-style-type: none"> - Thin-walled or unstable parts - Very tight tolerances - Medium quality surface finish

PCD cutting materials PU660/PU670














PU660	Application example: PISTON	
Fine grain PCD grade with carbide substrate. The fine grain lends the insert very good sharpness (chipping). The high wear resistance above all with abrasive materials gives this grade good tool lives also with tight tolerances.		Stock removal a_p : 0.5 mm Spindle speed: 3,700 rev/min Feed f: 0.12 mm Number of cutting edges: 1 Material: ALU B2+ Cooling: Emulsion Indexable insert: DCGT11T308






PU670	Application example: SHAFT	
PCD cutting material with medium particle size on a carbide substrate. Outstanding mechanical wear resistance and good ductility. Can also be used for milling operations.		Stock removal a_p : 0.3 mm Cutting speed: 800 m/min Feed f: 0.09 mm Diameter: 37 mm Length: 112 mm Material: AlMgSi0,5 Cooling: Emulsion Indexable insert: DCGT11T304

Chip breaker geometry for PU660 and PU670

Example	Geometry cutting material	Application description	Parameters for chip breaker geometry
	C1 PU660	The chip breaker structure C1 was specially developed for machining tasks with low cutting depths and therefore thin chips. The chips are also reliably broken at high cutting speeds and can be transported away without problems.	 Cutting depth in mm: 0, 0.3, 0.5, 0.8, 1, 1.5, 2 Feed f in mm/rev: 0.03, 0.05, 0.08, 0.1, 0.12, 0.15, 0.2, 0.25, 0.3
	C1 PU670	For machining tasks with high cutting depth, the structure C2 is available. Short, easy to control chips are also produced with this chip breaker structure.	 Cutting depth in mm: 0, 0.3, 0.5, 0.8, 1, 1.5, 2 Feed f in mm/rev: 0.03, 0.05, 0.08, 0.1, 0.12, 0.15, 0.2, 0.25, 0.3

Product overview PCD indexable inserts

Insert form	CCGT, single, one full length, normal/shortened	CCGT, single, one corner, normal	CCGT, single, one corner, C1/C2	CCGW, single, one full length, normal/shortened
C 				
Page	74	74	75	76
Insert form	DCGW, single, one corner, normal	DCGT, single, one corner, C1/C2	DPGW, single, one corner, normal	
D 				
Page	79	79	80	
Insert form	SCGT, single, one corner, normal	SCGT, single, one full length, normal/shortened	SCGT, single, one corner, C1/C2	SCGW, single, one corner, normal
S 				
Page	81	81	82	83
Insert form	TCGT, single, one corner, normal	TCGT, single, one full length, normal/shortened	TCGT, single, one corner, C1/C2	TPGW, single, one corner, normal
T 				
Page	86	86	87	87
Insert form	VBGW, single, one corner, normal	VBGT, single, one corner, C1	VCGW, single, one corner, normal	VCGT, single, one corner, C1
V 				
Page	89	89	89	89

CCGW, single, one corner,
normalCPGW, single, one full length,
normal/shortenedCPGW, single, one corner,
normalCPGT, single, one full length,
normal/shortenedCPGT, single, one corner,
normal






76

77

77

78

78

SCGW, single, one full length,
normal/shortenedSPGT, single, one corner,
normalSPGT, single, one full length,
normal/shortenedSPGW, single, one corner,
normalSPGW, single, one full length,
normal/shortened



83

84

84

85

85


TCGW, single, one corner,
normalTCGW, single, one full length,
normal/shortened

88

88

CCGT


PCD indexable insert, positive rake angle, shortened



Specification	Dimensions					PU620 F01
	d	s	r	d ₁	l ₁	
CCGT 060204 F01L-6LA	6,35	2,38	0,4	2,8	6,2	30249392
CCGT 060208 F01L-6LA	6,35	2,38	0,8	2,8	6,1	30249393
CCGT 09T304 F01L-6LA	9,52	3,97	0,4	4,4	9,4	30249394
CCGT 09T308 F01L-6LA	9,52	3,97	0,8	4,4	9,3	30249395
CCGT 120404 F01L-6LA	12,7	4,76	0,4	5,5	12,6	30249396
CCGT 120408 F01L-6LA	12,7	4,76	0,8	5,5	12,5	30249397
CCGT 060204 F01R-6LA	6,35	2,38	0,4	2,8	6,2	30249398
CCGT 060208 F01R-6LA	6,35	2,38	0,8	2,8	6,1	30249399
CCGT 09T304 F01R-6LA	9,52	3,97	0,4	4,4	9,4	30249400
CCGT 09T308 F01R-6LA	9,52	3,97	0,8	4,4	9,3	30249401
CCGT 120404 F01R-6LA	12,7	4,76	0,4	5,5	12,6	30249402
CCGT 120408 F01R-6LA	12,7	4,76	0,8	5,5	12,5	30249403

CCGT


PCD indexable insert, positive rake angle, normal



Specification	Dimensions					PU620 F01
	d	s	r	d ₁	l ₁	
CCGT 060204 F01L-1LA	6,35	2,38	0,4	2,8	6	30085694
CCGT 060208 F01L-1LA	6,35	2,38	0,8	2,8	5,6	30085695
CCGT 09T304 F01L-1LA	9,52	3,97	0,4	4,4	9,2	30085698
CCGT 09T308 F01L-1LA	9,52	3,97	0,8	4,4	8,8	30039803
CCGT 120404 F01L-1LA	12,7	4,76	0,4	5,5	12,5	30040424
CCGT 120408 F01L-1LA	12,7	4,76	0,8	5,5	12	30085701
CCGT 060204 F01R-1LA	6,35	2,38	0,4	2,8	6	30085721
CCGT 060208 F01R-1LA	6,35	2,38	0,8	2,8	5,6	30085722
CCGT 09T304 F01R-1LA	9,52	3,97	0,4	4,4	9,2	30039812
CCGT 09T308 F01R-1LA	9,52	3,97	0,8	4,4	8,8	30039811
CCGT 120404 F01R-1LA	12,7	4,76	0,4	5,5	12,5	30085727
CCGT 120408 F01R-1LA	12,7	4,76	0,8	5,5	12	30085728

CCGT

PCD indexable insert, positive rake angle





Specification	Dimensions					PU620 F01
	d	s	r	d ₁	l ₁	
CCGT 060204 F01N-5LA	6,35	2,38	0,4	2,8	3,1	30046179
CCGT 060208 F01N-5LA	6,35	2,38	0,8	2,8	3	30081181
CCGT 09T304 F01N-5LA	9,52	3,97	0,4	4,4	3,5	30029194
CCGT 09T308 F01N-5LA	9,52	3,97	0,8	4,4	3,4	30039802
CCGT 120404 F01N-5LA	12,7	4,76	0,4	5,5	4,7	30085663
CCGT 120408 F01N-5LA	12,7	4,76	0,8	5,5	4,6	30085664

Dimensions in mm.


CCGT

PCD indexable insert, chip breaker geometry C1



CCGT

PCD indexable insert, chip breaker geometry C2





Specification	Dimensions					PU660
	d	s	r	d ₁	l ₁	
CCGT 060202 F01N-C1A	6,35	2,38	0,2	2,8	3,4	10098159
CCGT 060204 F01N-C1A	6,35	2,38	0,4	2,8	3,2	10104313
CCGT 09T304 F01N-C1A	9,52	3,97	0,4	4,4	4,3	10099042
CCGT 09T308 F01N-C1A	9,52	3,97	0,8	4,4	4,1	30234050

Specification	Dimensions					PU670
	d	s	r	d ₁	l ₁	
CCGT 060202 F01N-C2A	6,35	2,38	0,2	2,8	3,4	30234059
CCGT 060204 F01N-C2A	6,35	2,38	0,4	2,8	3,2	30234060
CCGT 09T304 F01N-C2A	9,52	3,97	0,4	4,4	4,3	30234061
CCGT 09T308 F01N-C2A	9,52	3,97	0,8	4,4	4,1	30234062

CCGW



PCD indexable insert, 0° cutting angle, shortened



Specification	Dimensions					PU620 F01
	d	s	r	d ₁	l ₁	
CCGW 060204 F01L-6AA	6,35	2,38	0,4	2,8	6,2	30249380
CCGW 060208 F01L-6AA	6,35	2,38	0,8	2,8	6,1	30249381
CCGW 09T304 F01L-6AA	9,52	3,97	0,4	4,4	9,4	30249382
CCGW 09T308 F01L-6AA	9,52	3,97	0,8	4,4	9,3	30249383
CCGW 120404 F01L-6AA	12,7	4,76	0,4	5,5	12,6	30249384
CCGW 120408 F01L-6AA	12,7	4,76	0,8	5,5	12,5	30249385
CCGW 060204 F01R-6AA	6,35	2,38	0,4	2,8	6,2	30249386
CCGW 060208 F01R-6AA	6,35	2,38	0,8	2,8	6,1	30249387
CCGW 09T304 F01R-6AA	9,52	3,97	0,4	4,4	9,4	30249388
CCGW 09T308 F01R-6AA	9,52	3,97	0,8	4,4	9,3	30249389
CCGW 120404 F01R-6AA	12,7	4,76	0,4	5,5	12,6	30249390
CCGW 120408 F01R-6AA	12,7	4,76	0,8	5,5	12,5	30249391

CCGW



PCD indexable insert, 0° cutting angle, normal



Specification	Dimensions					PU620 F01
	d	s	r	d ₁	l ₁	
CCGW 060204 F01L-0AA	6,35	2,38	0,4	2,8	6	30034583
CCGW 060208 F01L-0AA	6,35	2,38	0,8	2,8	5,6	30034582
CCGW 09T304 F01L-0AA	9,52	3,97	0,4	4,4	9,2	30034581
CCGW 09T308 F01L-0AA	9,52	3,97	0,8	4,4	8,8	30030896
CCGW 120404 F01L-0AA	12,7	4,76	0,4	5,5	12,5	30034580
CCGW 120408 F01L-0AA	12,7	4,76	0,8	5,5	12	30085679
CCGW 060204 F01R-0AA	6,35	2,38	0,4	2,8	6	30041499
CCGW 060208 F01R-0AA	6,35	2,38	0,8	2,8	5,6	30085716
CCGW 09T304 F01R-0AA	9,52	3,97	0,4	4,4	9,2	30083391
CCGW 09T308 F01R-0AA	9,52	3,97	0,8	4,4	8,8	30036478
CCGW 120404 F01R-0AA	12,7	4,76	0,4	5,5	12,5	30085719
CCGW 120408 F01R-0AA	12,7	4,76	0,8	5,5	12	30085720

CCGW

PCD indexable insert, 0° rake angle




Specification	Dimensions					PU620 F01
	d	s	r	d ₁	l ₁	
CCGW 060204 F01N-0AA	6,35	2,38	0,4	2,8	3,1	30011027
CCGW 060208 F01N-0AA	6,35	2,38	0,8	2,8	3,0	30011028
CCGW 09T304 F01N-0AA	9,52	3,97	0,4	4,4	3,5	30011031
CCGW 09T308 F01N-0AA	9,52	3,97	0,8	4,4	3,4	30011032
CCGW 120404 F01N-0AA	12,7	4,76	0,4	5,5	4,7	30011033
CCGW 120408 F01N-0AA	12,7	4,76	0,8	5,5	4,6	30011034

Dimensions in mm.

CPGW


PCD indexable insert, 0° rake angle, shortened



Specification	Dimensions					PU620 F01
	d	s	r	d ₁	l ₁	
CPGW 060204 F01L-6AA	6,35	2,38	0,4	2,8	6,2	30249410
CPGW 060208 F01L-6AA	6,35	2,38	0,8	2,8	6,1	30249411
CPGW 09T304 F01L-6AA	9,52	3,97	0,4	4,4	9,4	30249412
CPGW 09T308 F01L-6AA	9,52	3,97	0,8	4,4	9,3	30249413
CPGW 060204 F01R-6AA	6,35	2,38	0,4	2,8	6,2	30249414
CPGW 060208 F01R-6AA	6,35	2,38	0,8	2,8	6,1	30249415
CPGW 09T304 F01R-6AA	9,52	3,97	0,4	4,4	9,4	30249416
CPGW 09T308 F01R-6AA	9,52	3,97	0,8	4,4	9,3	30249417

CPGW


PCD indexable insert, 0° rake angle, normal



Specification	Dimensions					PU620 F01
	d	s	r	d ₁	l ₁	
CPGW 060204 F01L-0AA	6,35	2,38	0,4	2,8	6	30036376
CPGW 060208 F01L-0AA	6,35	2,38	0,8	2,8	5,6	30085678
CPGW 09T304 F01L-0AA	9,52	3,97	0,4	4,4	9,2	30249406
CPGW 09T308 F01L-0AA	9,52	3,97	0,8	4,4	8,8	30249407
CPGW 060204 F01R-0AA	6,35	2,38	0,4	2,8	6	30040594
CPGW 060208 F01R-0AA	6,35	2,38	0,8	2,8	5,6	30085717
CPGW 09T304 F01R-0AA	9,52	3,97	0,4	4,4	9,2	30085790
CPGW 09T308 F01R-0AA	9,52	3,97	0,8	4,4	8,8	30249409

CPGW

PCD indexable insert, 0° rake angle




Specification	Dimensions					PU620 F01
	d	s	r	d ₁	l ₁	
CPGW 060204 F01N-0AA	6,35	2,38	0,4	2,8	3,1	30011029
CPGW 060208 F01N-0AA	6,35	2,38	0,8	2,8	3	30011030
CPGW 09T304 F01N-0AA	9,52	3,97	0,4	4,4	3,5	30085768
CPGW 09T308 F01N-0AA	9,52	3,97	0,8	4,4	3,4	30249405

Dimensions in mm.

CPGT


PCD indexable insert, positive rake angle, shortened



Specification	Dimensions					PU620 F01
	d	s	r	d ₁	l ₁	
CPGT 060204 F01L-6LA	6,35	2,38	0,4	2,8	6,2	30249424
CPGT 060208 F01L-6LA	6,35	2,38	0,8	2,8	6,1	30249425
CPGT 09T304 F01L-6LA	9,52	3,97	0,4	4,4	9,4	30249426
CPGT 09T308 F01L-6LA	9,52	3,97	0,8	4,4	9,3	30249427
CPGT 060204 F01R-6LA	6,35	2,38	0,4	2,8	6,2	30249428
CPGT 060208 F01R-6LA	6,35	2,38	0,8	2,8	6,1	30249429
CPGT 09T304 F01R-6LA	9,52	3,97	0,4	4,4	9,4	30249430
CPGT 09T308 F01R-6LA	9,52	3,97	0,8	4,4	9,3	30249431

CPGT


PCD indexable insert, positive rake angle, normal



Specification	Dimensions					PU620 F01
	d	s	r	d ₁	l ₁	
CPGT 060204 F01L-1LA	6,35	2,38	0,4	2,8	6	30085696
CPGT 060208 F01L-1LA	6,35	2,38	0,8	2,8	5,6	30085697
CPGT 09T304 F01L-1LA	9,52	3,97	0,4	4,4	9,2	30249420
CPGT 09T308 F01L-1LA	9,52	3,97	0,8	4,4	8,8	30249421
CPGT 060204 F01R-1LA	6,35	2,38	0,4	2,8	6	30085723
CPGT 060208 F01R-1LA	6,35	2,38	0,8	2,8	5,6	30085724
CPGT 09T304 F01R-1LA	9,52	3,97	0,4	4,4	9,2	30249422
CPGT 09T308 F01R-1LA	9,52	3,97	0,8	4,4	8,8	30249423

CPGT


PCD indexable insert, positive rake angle



Specification	Dimensions					PU620 F01
	d	s	r	d ₁	l ₁	
CPGT 060204 F01N-5LA	6,35	2,38	0,2	2,8	3,1	30085661
CPGT 060208 F01N-5LA	6,35	2,38	0,4	2,8	3	30085662
CPGT 09T304 F01N-5LA	9,52	3,97	0,4	4,4	3,5	30249418
CPGT 09T308 F01N-5LA	9,52	3,97	0,8	4,4	3,4	30249419

DCGW


PCD indexable insert, 0° rake angle



Specification	Dimensions					PU620
	d	s	r	d ₁	l ₁	
DCGW 070202 F01N-0AA	6,35	2,38	0,2	2,8	3,7	30249512
DCGW 070204 F01N-0AA	6,35	2,38	0,4	2,8	3,4	30249513
DCGW 070208 F01N-0AA	6,35	2,38	0,8	2,8	3	30249514
DCGW 11T304 F01N-0AA	9,52	3,97	0,4	4,4	3,9	30234072
DCGW 11T308 F01N-0AA	9,52	3,97	0,8	4,4	3,5	30234073

DCGT


PCD indexable insert, chip breaker geometry C1



Specification	Dimensions					PU660
	d	s	r	d ₁	l ₁	
DCGT 070202 F01N-C1A	6,35	2,38	0,2	2,8	3,7	30223531
DCGT 070204 F01N-C1A	6,35	2,38	0,4	2,8	3,4	10104930
DCGT 11T302 F01N-C1A	9,52	3,97	0,2	4,4	4,7	30234051
DCGT 11T304 F01N-C1A	9,52	3,97	0,4	4,4	4,3	30234052
DCGT 11T308 F01N-C1A	9,52	3,97	0,8	4,4	4	30234053

DCGT


PCD indexable insert, chip breaker geometry C2



Specification	Dimensions					PU670
	d	s	r	d ₁	l ₁	
DCGT 070202 F01N-C2A	6,35	2,38	0,2	2,8	3,7	30234063
DCGT 070204 F01N-C2A	6,35	2,38	0,4	2,8	3,4	30234064
DCGT 11T302 F01N-C2A	9,52	3,97	0,2	4,4	4,7	30234065
DCGT 11T304 F01N-C2A	9,52	3,97	0,4	4,4	4,3	30234066
DCGT 11T308 F01N-C2A	9,52	3,97	0,8	4,4	4	30234067

DPGW


PCD indexable insert, 0° rake angle



Specification	Dimensions					PU620
	d	s	r	d ₁	l ₁	
DPGW 070202 F01N-0AA	6,35	2,38	0,2	2,8	3,7	30257651
DPGW 070204 F01N-0AA	6,35	2,38	0,4	2,8	3,4	30257654
DPGW 070208 F01N-0AA	6,35	2,38	0,8	2,8	3	30257656
DPGW 11T304 F01N-0AA	9,52	3,97	0,4	4,4	3,9	30257657
DPGW 11T308 F01N-0AA	9,52	3,97	0,8	4,4	3,5	30257660

SCGT


PCD indexable insert, positive rake angle



Specification	Dimensions					PU620 F01
	d	s	r	d ₁	l ₁	
SCGT 060204 F01N-5LA	6,35	2,38	0,4	2,8	2,8	30085665
SCGT 060208 F01N-5LA	6,35	2,38	0,8	2,8	2,8	30085666
SCGT 09T304 F01N-5LA	9,52	3,97	0,4	2,8	3,1	30037904
SCGT 09T308 F01N-5LA	9,52	3,97	0,8	4,4	3,1	30058354
SCGT 120404 F01N-5LA	12,7	4,76	0,4	5,5	4,5	30085670
SCGT 120408 F01N-5LA	12,7	4,76	0,8	5,5	4,5	30039810

SCGT


PCD indexable insert, positive rake angle, normal



Specification	Dimensions					PU620 F01
	d	s	r	d ₁	l ₁	
SCGT 060204 F01X-1LA	6,35	2,38	0,4	2,8	5,9	30085702
SCGT 060208 F01X-1LA	6,35	2,38	0,8	2,8	5,5	30085703
SCGT 09T304 F01X-1LA	9,52	3,97	0,4	4,4	9,1	30047583
SCGT 09T308 F01X-1LA	9,52	3,97	0,8	4,4	8,7	30085707
SCGT 120404 F01X-1LA	12,7	4,76	0,4	5,5	12,3	30085708
SCGT 120408 F01X-1LA	12,7	4,76	0,8	5,5	11,9	30085709

SCGT

PCD indexable insert, positive rake angle, shortened




Specification	Dimensions					PU620 F01
	d	s	r	d ₁	l ₁	
SCGT 060204 F01L-6LA	6,35	2,38	0,4	2,8	6,2	30249444
SCGT 060208 F01L-6LA	6,35	2,38	0,8	2,8	6,2	30249445
SCGT 09T304 F01L-6LA	9,52	3,97	0,4	4,4	9,3	30249446
SCGT 09T308 F01L-6LA	9,52	3,97	0,8	4,4	9,3	30249447
SCGT 120404 F01L-6LA	12,7	4,76	0,4	5,5	12,4	30249448
SCGT 120408 F01L-6LA	12,7	4,76	0,8	5,5	12,4	30249449
SCGT 060204 F01R-6LA	6,35	2,38	0,4	2,8	6,2	30249450
SCGT 060208 F01R-6LA	6,35	2,38	0,8	2,8	6,2	30249451
SCGT 09T304 F01R-6LA	9,52	3,97	0,4	4,4	9,3	30249452
SCGT 09T308 F01R-6LA	9,52	3,97	0,8	4,4	9,3	30249453
SCGT 120404 F01R-6LA	12,7	4,76	0,4	5,5	12,4	30249454
SCGT 120408 F01R-6LA	12,7	4,76	0,8	5,5	12,4	30249455

Dimensions in mm.


SCGT

PCD indexable insert, chip breaker geometry C1



SCGT

PCD indexable insert, chip breaker geometry C2





Specification	Dimensions					PU660
	d	s	r	d ₁	l ₁	
SCGT 09T304 F01N-C1A	9,52	3,97	0,4	4,4	4,4	F01 30250260
SCGT 09T308 F01N-C1A	9,52	3,97	0,8	4,4	4,3	30250261
SCGT 120404 F01N-C1A	12,7	4,76	0,4	5,5	4,4	30250262
SCGT 120408 F01N-C1A	12,7	4,76	0,8	5,5	4,3	30250263

Specification	Dimensions					PU670
	d	s	r	d ₁	l ₁	
SCGT 09T304 F01N-C2A	6,35	2,38	0,4	4,4	4,4	30249456
SCGT 09T308 F01N-C2A	6,35	2,38	0,8	4,4	4,3	30249457
SCGT 120404 F01N-C2A	9,52	3,97	0,4	5,5	4,4	30249458
SCGT 120408 F01N-C2A	9,52	3,97	0,8	5,5	4,3	30249459

SCGW



PCD indexable insert, 0° rake angle



Specification	Dimensions					PU620 F01
	d	s	r	d ₁	l ₁	
SCGW 060204 F01N-0AA	6,35	2,38	0,4	2,8	2,8	30011035
SCGW 060208 F01N-0AA	6,35	2,38	0,8	2,8	2,8	30011036
SCGW 09T304 F01N-0AA	9,52	3,97	0,4	2,8	3,1	30011037
SCGW 09T308 F01N-0AA	9,52	3,97	0,8	4,4	3,1	30011038
SCGW 120404 F01N-0AA	12,7	4,76	0,4	5,5	4,5	30011039
SCGW 120408 F01N-0AA	12,7	4,76	0,8	5,5	4,5	30011040

SCGW



PCD indexable insert, 0° rake angle, normal



Specification	Dimensions					PU620 F01
	d	s	r	d ₁	l ₁	
SCGW 060204 F01X-0AA	6,35	2,38	0,4	2,8	5,9	30085680
SCGW 060208 F01X-0AA	6,35	2,38	0,8	2,8	5,5	30085681
SCGW 09T304 F01X-0AA	9,52	3,97	0,4	4,4	9,1	30025529
SCGW 09T308 F01X-0AA	9,52	3,97	0,8	4,4	8,7	30037231
SCGW 120404 F01X-0AA	12,7	4,76	0,4	5,5	12,3	30083392
SCGW 120408 F01X-0AA	12,7	4,76	0,8	5,5	11,9	30085687

SCGW

PCD indexable insert, 0° rake angle, shortened





Specification	Dimensions					PU620 F01
	d	s	r	d ₁	l ₁	
SCGW 060204 F01L-6AA	6,35	2,38	0,4	2,8	6,2	30249432
SCGW 060208 F01L-6AA	6,35	2,38	0,8	2,8	6,2	30249433
SCGW 09T304 F01L-6AA	9,52	3,97	0,4	4,4	9,3	30249434
SCGW 09T308 F01L-6AA	9,52	3,97	0,8	4,4	9,3	30249435
SCGW 120404 F01L-6AA	12,7	4,76	0,4	5,5	12,4	30249436
SCGW 120408 F01L-6AA	12,7	4,76	0,8	5,5	12,4	30249437
SCGW 060204 F01R-6AA	6,35	2,38	0,4	2,8	6,2	30249438
SCGW 060208 F01R-6AA	6,35	2,38	0,8	2,8	6,2	30249439
SCGW 09T304 F01R-6AA	9,52	3,97	0,4	4,4	9,3	30249440
SCGW 09T308 F01R-6AA	9,52	3,97	0,8	4,4	9,3	30249441
SCGW 120404 F01R-6AA	12,7	4,76	0,4	5,5	12,4	30249442
SCGW 120408 F01R-6AA	12,7	4,76	0,8	5,5	12,4	30249443

Dimensions in mm.

SPGT



PCD indexable insert, positive rake angle



Specification	Dimensions					PU620 F01
	d	s	r	d ₁	l ₁	
SPGT 060304 F01N-5LA	6,35	3,18	0,4	2,8	2,8	30049511
SPGT 060308 F01N-5LA	6,35	3,18	0,8	2,8	2,8	30085668
SPGT 09T304 F01N-5LA	9,52	3,97	0,4	4,4	3,1	30249472
SPGT 09T308 F01N-5LA	9,52	3,97	0,8	4,4	3,1	30249473

SPGT



PCD indexable insert, positive rake angle, normal



Specification	Dimensions					PU620 F01
	d	s	r	d ₁	l ₁	
SPGT 060304 F01X-1LA	6,35	3,18	0,4	2,8	5,9	30040407
SPGT 060308 F01X-1LA	6,35	3,18	0,8	2,8	5,5	30085705
SPGT 09T304 F01X-1LA	9,52	3,97	0,4	4,4	9,1	30249474
SPGT 09T308 F01X-1LA	9,52	3,97	0,8	4,4	8,7	30249475

SPGT



PCD indexable insert, positive rake angle, shortened



Specification	Dimensions					PU620 F01
	d	s	r	d ₁	l ₁	
SPGT 060304 F01L-6LA	6,35	3,18	0,4	2,8	6,2	30249476
SPGT 060308 F01L-6LA	6,35	3,18	0,8	2,8	6,2	30249477
SPGT 09T304 F01L-6LA	9,52	3,97	0,4	4,4	9,3	30249478
SPGT 09T308 F01L-6LA	9,52	3,97	0,8	4,4	9,3	30249479
SPGT 060304 F01R-6LA	6,35	3,18	0,4	2,8	6,2	30249480
SPGT 060308 F01R-6LA	6,35	3,18	0,8	2,8	6,2	30249481
SPGT 09T304 F01R-6LA	9,52	3,97	0,4	4,4	9,3	30249482
SPGT 09T308 F01R-6LA	9,52	3,97	0,8	4,4	9,3	30249483

SPGW



PCD indexable insert, 0° rake angle



Specification	Dimensions					PU620 F01
	d	s	r	d ₁	l ₁	
SPGW 060304 F01N-0AA	6,35	3,18	0,4	2,8	2,8	30036253
SPGW 060308 F01N-0AA	6,35	3,18	0,8	2,8	2,8	30085658
SPGW 09T304 F01N-0AA	9,52	3,97	0,4	4,4	3,1	30249460
SPGW 09T308 F01N-0AA	9,52	3,97	0,8	4,4	3,1	30249461

SPGW



PCD indexable insert, 0° rake angle, normal



Specification	Dimensions					PU620 F01
	d	s	r	d ₁	l ₁	
SPGW 060304 F01X-0AA	6,35	3,18	0,4	2,8	5,9	30085682
SPGW 060308 F01X-0AA	6,35	3,18	0,8	2,8	5,5	30085683
SPGW 09T304 F01X-0AA	9,52	3,97	0,4	4,4	9,1	30039129
SPGW 09T308 F01X-0AA	9,52	3,97	0,8	4,4	8,7	30249463

SPGW

PCD indexable insert, 0° rake angle, shortened




Specification	Dimensions					PU620 F01
	d	s	r	d ₁	l ₁	
SPGW 060304 F01L-6AA	6,35	3,18	0,4	2,8	6,2	30249464
SPGW 060308 F01L-6AA	6,35	3,18	0,8	2,8	6,2	30249465
SPGW 09T304 F01L-6AA	9,52	3,97	0,4	4,4	9,3	30249466
SPGW 09T308 F01L-6AA	9,52	3,97	0,8	4,4	9,3	30249467
SPGW 060304 F01R-6AA	6,35	3,18	0,4	2,8	6,2	30249468
SPGW 060308 F01R-6AA	6,35	3,18	0,8	2,8	6,2	30249469
SPGW 09T304 F01R-6AA	9,52	3,97	0,4	4,4	9,3	30249470
SPGW 09T308 F01R-6AA	9,52	3,97	0,8	4,4	9,3	30249471

Dimensions in mm.

TCGT


PCD indexable insert, positive rake angle



Specification	Dimensions					PU620 F01
	d	s	r	d ₁	l ₁	
TCGT 090204 F01N-5LA	5,56	2,38	0,4	2,5	3,4	30085671
TCGT 090208 F01N-5LA	5,56	2,38	0,8	2,5	3,1	30085672
TCGT 110204 F01N-5LA	6,35	2,38	0,4	2,8	3,8	30085673
TCGT 110208 F01N-5LA	6,35	2,38	0,8	2,8	3,5	30085674
TCGT 16T304 F01N-5LA	9,52	3,97	0,4	4,4	5,4	30085675
TCGT 16T308 F01N-5LA	9,52	3,97	0,8	4,4	5,1	30085676

TCGT


PCD indexable insert, positive rake angle, normal



Specification	Dimensions					PU620 F01
	d	s	r	d ₁	l ₁	
TCGT 090204 F01X-1LA	5,56	2,38	0,4	2,5	8,6	30085710
TCGT 090208 F01X-1LA	5,56	2,38	0,8	2,5	7,6	30085711
TCGT 110204 F01X-1LA	6,35	2,38	0,4	2,8	10	30085712
TCGT 110208 F01X-1LA	6,35	2,38	0,8	2,8	9	30085713
TCGT 16T304 F01X-1LA	9,52	3,97	0,4	4,4	15,5	30085714
TCGT 16T308 F01X-1LA	9,52	3,97	0,8	4,4	14,5	30085715

TCGT


PCD indexable insert, positive rake angle, shortened



Specification	Dimensions					PU620 F01
	d	s	r	d ₁	l ₁	
TCGT 090204 F01L-6LA	5,56	2,38	0,4	2,5	8,6	30249496
TCGT 090208 F01L-6LA	5,56	2,38	0,8	2,5	8,3	30249497
TCGT 110204 F01L-6LA	6,35	2,38	0,4	2,8	9,8	30249498
TCGT 110208 F01L-6LA	6,35	2,38	0,8	2,8	9,5	30249499
TCGT 16T304 F01L-6LA	9,52	3,97	0,4	4,4	15	30249500
TCGT 16T308 F01L-6LA	9,52	3,97	0,8	4,4	14,7	30249501
TCGT 090204 F01R-6LA	5,56	2,38	0,4	2,5	8,6	30249502
TCGT 090208 F01R-6LA	5,56	2,38	0,8	2,5	8,3	30249503
TCGT 110204 F01R-6LA	6,35	2,38	0,4	2,8	9,8	30249504
TCGT 110208 F01R-6LA	6,35	2,38	0,8	2,8	9,5	30249505
TCGT 16T304 F01R-6LA	9,52	3,97	0,4	4,4	15	30249506
TCGT 16T308 F01R-6LA	9,52	3,97	0,8	4,4	14,7	30249507

TCGT


PCD indexable insert, chip breaker geometry C1



Specification	Dimensions					PU660
	d	s	r	d ₁	l ₁	
TCGT 110202 F01N-C1A	6,35	2,38	0,2	2,8	3,7	30234054
TCGT 110204 F01N-C1A	6,35	2,38	0,4	2,8	3,4	30234055

TCGT


PCD indexable insert, chip breaker geometry C2



Specification	Dimensions					PU670
	d	s	r	d ₁	l ₁	
TCGT 110202 F01N-C2A	6,35	2,38	0,2	2,8	3,7	30250264
TCGT 110204 F01N-C2A	6,35	2,38	0,4	2,8	3,4	30250265

TPGW

PCD indexable insert, 0° rake angle




Specification	Dimensions					PU620
	d	s	r	d ₁	l ₁	
TPGW 090204 F01N-0AA	5,56	2,38	0,4	2,5	3,4	30252340
TPGW 090208 F01N-0AA	5,56	2,38	0,8	2,5	3,1	30257663
TPGW 110204 F01N-0AA	6,35	2,38	0,4	2,8	3,8	30257665
TPGW 110208 F01N-0AA	6,35	2,38	0,8	2,8	3,5	30257666
TPGW 16T304 F01N-0AA	9,52	3,97	0,4	4,4	5,4	30257668
TPGW 16T308 F01N-0AA	9,52	3,97	0,8	4,4	5,1	30257670

Dimensions in mm.

TCGW


PCD indexable insert, 0° rake angle



Specification	Dimensions					PU620 F01
	d	s	r	d ₁	l ₁	
TCGW 090204 F01N-0AA	5,56	2,38	0,4	2,5	3,4	30011041
TCGW 090208 F01N-0AA	5,56	2,38	0,8	2,5	3,1	30011042
TCGW 110204 F01N-0AA	6,35	2,38	0,4	2,8	3,8	30011043
TCGW 110208 F01N-0AA	6,35	2,38	0,8	2,8	3,5	30011044
TCGW 16T304 F01N-0AA	9,52	3,97	0,4	4,4	5,4	30011045
TCGW 16T308 F01N-0AA	9,52	3,97	0,8	4,4	5,1	30011046

TCGW


PCD indexable insert, 0° rake angle, normal



Specification	Dimensions					PU620 F01
	d	s	r	d ₁	l ₁	
TCGW 090204 F01X-0AA	5,56	2,38	0,4	2,5	7,9	30085688
TCGW 090208 F01X-0AA	5,56	2,38	0,8	2,5	7,6	30085689
TCGW 110204 F01X-0AA	6,35	2,38	0,4	2,8	10	30034491
TCGW 110208 F01X-0AA	6,35	2,38	0,8	2,8	9	30085691
TCGW 16T304 F01X-0AA	9,52	3,97	0,4	4,4	15,5	30085692
TCGW 16T308 F01X-0AA	9,52	3,97	0,8	4,4	14,5	30085693

TCGW

PCD indexable insert, 0° rake angle, shortened




Specification	Dimensions					PU620 F01
	d	s	r	d ₁	l ₁	
TCGW 090204 F01L-6AA	5,56	2,38	0,4	2,5	8,6	30249484
TCGW 090208 F01L-6AA	5,56	2,38	0,8	2,5	8,3	30249485
TCGW 110204 F01L-6AA	6,35	2,38	0,4	2,8	9,8	30249486
TCGW 110208 F01L-6AA	6,35	2,38	0,8	2,8	9,5	30249487
TCGW 16T304 F01L-6AA	9,52	3,97	0,4	4,4	15	30249488
TCGW 16T308 F01L-6AA	9,52	3,97	0,8	4,4	14,7	30249489
TCGW 090204 F01R-6AA	5,56	2,38	0,4	2,5	8,6	30249490
TCGW 090208 F01R-6AA	5,56	2,38	0,8	2,5	8,3	30249491
TCGW 110204 F01R-6AA	6,35	2,38	0,4	2,8	9,8	30249492
TCGW 110208 F01R-6AA	6,35	2,38	0,8	2,8	9,5	30249493
TCGW 16T304 F01R-6AA	9,52	3,97	0,4	4,4	15	30249494
TCGW 16T308 F01R-6AA	9,52	3,97	0,8	4,4	14,7	30249495

Dimensions in mm.

VBGW


PCD indexable insert, 0° rake angle



Specification	Dimensions					PU620
	d	s	r	d ₁	l ₁	
VBGW 160404 F01N-0AA	9,52	4,76	0,4	4,4	5,5	F01 30249508
VBGW 160408 F01N-0AA	9,52	4,76	0,8	4,4	5	30249509

VBGT


PCD indexable insert, chip breaker geometry C1



Specification	Dimensions					PU660
	d	s	r	d ₁	l ₁	
VBGT 160404 F01N-C1A	9,52	4,76	0,4	4,4	5,5	30234056
VBGT 160408 F01N-C1A	9,52	4,76	0,8	4,4	5	30234057

VCGW


PCD indexable insert, 0° rake angle



Specification	Dimensions					PU620
	d	s	r	d ₁	l ₁	
VCGW 160404 F01N-0AA	9,52	4,76	0,4	4,4	5,5	30249510
VCGW 160408 F01N-0AA	9,52	4,76	0,8	4,4	5	30249511

VCgt

PCD indexable insert, chip breaker geometry C1



Specification	Dimensions					PU660
	d	s	r	d ₁	l ₁	
VCgt 110302 F01N-C1A	6,35	3,18	0,2	2,9	4,6	30234058
VCgt 110304 F01N-C1A	6,35	3,18	0,4	2,9	3,9	30223530
VCgt 160404 F01N-C1A	9,52	4,76	0,4	4,4	5,5	10105369
VCgt 160408 F01N-C1A	9,52	4,76	0,8	4,4	5	30228625



HSK-T

ISO turning tools and conversion systems







TOOLS WITH HSK-T CONNECTION

Introduction

Designation key 96

Product overview turning holders HSK-T 98

Tools with HSK-T connection

Turning holders HSK-T 40, 63, 100 with negative indexable blade 100

Turning holders HSK-T 40, 63, 100 with positive indexable blade 115

Shank holders HSK-T 40, 63, 100 124

Spare parts 128

HSK-T – THE STANDARDISED HOLLOW SHANK TAPER FOR TURNING

HSK as a connection stands for high precision and rigidity; it is very robust and straightforward to design and manufacture. HSK has established itself – whether on machining centres with automatic tool changers or on custom machines and transfer lines with manual tool clamping.

To be able to utilise the advantages of HSK also for usage on lathes or turning-milling centres, the HSK-T standard (T = Turning) was developed. Compared to other HSK variants the driving element play on the HSK-T is limited and in this way the effect on the position of the insert minimised.

The HSK-T also plays on its advantages during the complete machining of cubic parts and turning workpieces with cross bores, threads or milling tasks on turning-milling centres. It can be used as a universal connection for rotating and stationary tools and makes possible minimum set-up and tool changing times. The changing times for tools reduce to less than 30 seconds with the HSK connection. Ten to 15 minutes are normal here with other standardised systems.

Using the HSK-T connection a high degree of flexibility is achieved during the cost-effective production of complex parts, even with smaller

batch sizes and a large variance between the parts. The high changeover accuracy of the HSK-T makes it possible to provide sister tools that are pre-set and measured on the setting up station and are used directly on the revolver. No samples or corrections are necessary at all. HSK-T as a tool connection is independently standardised across sectors. In this way a large number of possibilities and alternatives open up. The user is not bound to only a few manufacturers as with other quick-change systems. The costs for new HSK-T tools and holders are quickly re-paid due to the enormous time-saving during revolver changeover and the tool change.

MAPAL offers a complete turning holder programme in the sizes HSK-T 40, 63 and 100. In this way almost all turning methods are covered. The tools can be operated with HSK-A tool changers, which ensures a very high degree of flexibility.

ADVANTAGES

- Stationary and also powered tools can be used on the same clamping station; it is not necessary to change over the revolver
- High changeover accuracy and accuracy of repetition
- High fit accuracy
- High rigidity
- Exact radial positioning accuracy
- Manufacturer-independent
- High flexibility of the HSK connection
- Straightforward manufacture
- Short set-up times
- Existing HSK-A tools can be re-used
- Possible to work with pre-set tools also on turret
- Can be used with MQL
- Reduced non-productive times
- With HSK-T only one connection required on turning-milling centres





HSK-T in detail


Due to the limited driving element play, the connection centres itself on clamping the tool.
As a result height of the centre line for the tool is reached exactly.



Designation key


Tools with HSK-T connection

Turning holder HSK-T



Series/type	Shank design	Shank size	Insert clamping clamping system	Indexable insert form	Holder shape
MTH HSK-T turning holder	HSK	T040 HSK-T40 T063 HSK-T63 T100 HSK-T100	C Clamped from above D Clamped from above and via bore M Clamped from above with bore P Toggle lever clamping S Screwed through bore	C 80 ° D 55 ° S 90 ° V 35 ° W 80 °	A 90 ° B 75 ° D 45 ° E 60 ° G 90 ° H 107.5 ° J 93 ° L 95 ° M 50 ° N 62.5 ° P 117.5 ° Q 107.5 ° R 75 ° S 45 ° U 93 ° V 72.5 °

Shank holder with HSK-T



Series/type	Shank design	Shank size	Holder
MTH HSK-T turning holder	HSK	T040 HSK-T40 T063 HSK-T63 T100 HSK-T100	BH For cylindrical shank SH For square shank

N R - 1 5 0 - 3 2 - 1 6

Insert clearance angle

B	5 °
C	7 °
N	0 °

Machining direction

R	Right
L	Left
N	Neutral

l_1 [mm]

f [mm]

Insert size

Shank holder
for square connections

2 R 00 - 2020

Design

2	Double
3	Triple

Cutting direction

R	Right
L	Left
N	Neutral

Index

00	Axial
45	Diagonal
90	Radial

Connection size

2020	20x20
2525	25x25

Shank holder
for cylindrical connection

06 - 055

d_1 [mm]

l_1 [mm]















Product overview turning holders HSK-T

Turning holders with negative indexable insert

Insert form	DCLN... I PCLN... 95°/80°	DCMNN I PCMNN 50°/80°/50°	DCLN... I PCLN..., long 95°/80°		
c					
Page	100	101	111, 112		
Insert form	DDHN... I PDHN... 107.5 °/55 °	DDJN... I PDJN... 55 °/93 °	DDNNN I PDNNN 62.5 °/55 °/62.5 °	DDUN... I PDUN... 93 °/55 °	DDQN... I PDQN..., long 107.5 °/55 °
d					
Page	102	103	104	105	113, 114
Insert form	DSBN... I PSBN... 90 °/75 °	DSSN... I PSSN... 45 °/90 °			
s					
Page	106	107			
Insert form	DVPNR I DVPNL 117.5 °/35 °	DVUNR I DVUNL 93 °/35 °	DVVNN 72.5 °/35 °/72.5 °	DVJNR I DVJNL 93 °/35 °	
v					
Page	108	108	109	109	
Insert form	DWLN... I PWLN... 95°/80°				
w					
Page	110				


Product overview turning holders HSK-T

Turning holders with positive indexable insert

Insert form	SCLCR I SCLCL 95°/80°	SCMCN 50°/80°/50°	SCLC... long 95°/80°		
					
Page	115	115	122		
Insert form	SDHCR I SDHCL 107.5 °/55 °	SDNCN 62.5 °/55 °/62.5 °	SDJCR I SDJCL 93 °/55 °	SDUCR I SDUCL 93 °/55 °	SDQC..., long 107.5 °/55 °
					
Page	116	116	117	117	123
Insert form	SSBCR I SSBCL 75 °/90 °	SSSCR I SSSCL 45 °/90 °			
					
Page	118	118			
Insert form	SVPB... I SVPC... 117.5 °/35 °	SVUB... I SVUC... 93 °/35 °	SVVB... I SVVC... 72.5 °/35 °/72.5 °	SVJB... I SVJC... 93 °/35 °	
					
Page	119	120	121	121	

HSK-T turning holders

DCLN... | PCLN...




Turning holders DCLNR | DCLNL 95°/80°

Negative indexable insert



Nominal size HSK-T	Dimensions			Direction of rotation	Insert	Specification	Order No.
	f	d ₁ min	l ₁				
40	27	50	55	R	CN..1204..	MTH-HSK-T040-DCLNR-055-27-12	30335748
40	27	50	55	L	CN..1204..	MTH-HSK-T040-DCLNL-055-27-12	30335749
63	45	80	70	R	CN..1204..	MTH-HSK-T063-DCLNR-070-45-12	30609486
63	45	80	70	L	CN..1204..	MTH-HSK-T063-DCLNL-070-45-12	30609487
63	45	80	70	R	CN..1606..	MTH-HSK-T063-DCLNR-070-45-16	30609488
63	45	80	70	L	CN..1606..	MTH-HSK-T063-DCLNL-070-45-16	30609489
100	63	120	100	R	CN..1204..	MTH-HSK-T100-DCLNR-100-63-12	30609490
100	63	120	100	L	CN..1204..	MTH-HSK-T100-DCLNL-100-63-12	30609491
100	63	120	100	R	CN..1606..	MTH-HSK-T100-DCLNR-100-63-19	30609492
100	63	120	100	L	CN..1606..	MTH-HSK-T100-DCLNL-100-63-19	30609493



Turning holders PCLNR | PCLNL 95°/80°

Negative indexable insert

Nominal size HSK-T	Dimensions			Direction of rotation	Insert	Specification	Order No.
	f	d ₁ min	l ₁				
40	27	50	55	R	CN..1204..	MTH-HSK-T040-PCLNR-055-27-12	30335750
40	27	50	55	L	CN..1204..	MTH-HSK-T040-PCLNL-055-27-12	30335751
63	45	80	70	R	CN..1204..	MTH-HSK-T063-PCLNR-070-45-12	30609494
63	45	80	70	L	CN..1204..	MTH-HSK-T063-PCLNL-070-45-12	30609495
63	45	80	70	R	CN..1606..	MTH-HSK-T063-PCLNR-070-45-16	30609496
63	45	80	70	L	CN..1606..	MTH-HSK-T063-PCLNL-070-45-16	30609497
100	63	120	100	R	CN..1204..	MTH-HSK-T100-PCLNR-100-63-12	30609498
100	63	120	100	L	CN..1204..	MTH-HSK-T100-PCLNL-100-63-12	30609499
100	63	120	100	R	CN..1606..	MTH-HSK-T100-PCLNR-100-63-16	30609500
100	63	120	100	L	CN..1606..	MTH-HSK-T100-PCLNL-100-63-16	30609501


Dimensions in mm.

You will find accessories and spare parts on pages 128-130.

You will find information on the HSK standard and fitting dimensions, as well as on the shank position and position of the slots in the section "Technical appendix".

HSK-T turning holders

DCMNN | PCMNN




Turning holders DCMNN 50°/80°/50°

Negative indexable insert



Nominal size HSK-T	Dimensions			Direction of rotation	Insert	Specification	Order No.
	f	d ₁ min	l ₁				
40	-	-	80	N	CN..1204..	MTH-HSK-T040-DCMNN-080-00-12	30335779
63	-	-	100	N	CN..1204..	MTH-HSK-T063-DCMNN-100-00-12	30609502
63	-	-	130	N	CN..1204..	MTH-HSK-T063-DCMNN-130-00-12	30609503
63	-	-	100	N	CN..1606..	MTH-HSK-T063-DCMNN-100-00-12	30609504
63	-	-	130	N	CN..1606..	MTH-HSK-T063-DCMNN-130-00-12	30609505
100	-	-	125	N	CN..1204..	MTH-HSK-T100-DCMNN-125-00-12	30609506
100	-	-	125	N	CN..1606..	MTH-HSK-T100-DCMNN-125-00-12	30609507



Turning holders PCMNN 50°/80°/50°

Negative indexable insert



Nominal size HSK-T	Dimensions			Direction of rotation	Insert	Specification	Order No.
	f	d ₁ min	l ₁				
40	-	-	80	N	CN..1204..	MTH-HSK-T040-PCMNN-080-00-12	30335780
63	-	-	100	N	CN..1204..	MTH-HSK-T063-PCMNN-100-00-12	30609508
63	-	-	130	N	CN..1204..	MTH-HSK-T063-PCMNN-130-00-12	30609509
63	-	-	100	N	CN..1606..	MTH-HSK-T063-PCMNN-100-00-12	30609510
63	-	-	130	N	CN..1606..	MTH-HSK-T063-PCMNN-130-00-12	30609511
100	-	-	125	N	CN..1204..	MTH-HSK-T100-PCMNN-125-00-12	30609512
100	-	-	125	N	CN..1606..	MTH-HSK-T100-PCMNN-125-00-12	30609513


Dimensions in mm.

You will find accessories and spare parts on pages 128-130.

You will find information on the HSK standard and fitting dimensions, as well as on the shank position and position of the slots in the section "Technical appendix".

HSK-T turning holders

DDHN... | PDHN...




Turning holders DDHNR | DDHNL 107.5°/55°

Negative indexable insert



Nominal size HSK-T	Dimensions			Direction of rotation	Insert	Specification	Order No.
	f	d ₁ min	l ₁				
40	27	50	55	R	DN..1506..	MTH-HSK-T040-DDHNR-055-27-15	30462004
40	27	50	55	L	DN..1506..	MTH-HSK-T040-DDHNL-055-27-15	30462005
63	45	80	70	R	DN..1506..	MTH-HSK-T063-DDHNR-070-45-15	30609514
63	45	80	70	L	DN..1506..	MTH-HSK-T063-DDHNL-070-45-15	30609515
100	63	120	100	R	DN..1506..	MTH-HSK-T100-DDHNR-100-63-15	30609516
100	63	120	100	L	DN..1506..	MTH-HSK-T100-DDHNL-100-63-15	30609517



Turning holders PDHNR | PDHNL 107.5°/55°

Negative indexable insert



Nominal size HSK-T	Dimensions			Direction of rotation	Insert	Specification	Order No.
	f	d ₁ min	l ₁				
40	27	50	55	R	DN..1506..	MTH-HSK-T040-PDHNR-055-27-15	30335756
40	27	50	55	L	DN..1506..	MTH-HSK-T040-PDHNL-055-27-15	30335757
63	45	80	70	R	DN..1506..	MTH-HSK-T063-PDHNR-070-45-15	30609518
63	45	80	70	L	DN..1506..	MTH-HSK-T063-PDHNL-070-45-15	30609519
100	63	120	100	R	DN..1506..	MTH-HSK-T100-PDHNR-100-63-15	30609520
100	63	120	100	L	DN..1506..	MTH-HSK-T100-PDHNL-100-63-15	30609521


Dimensions in mm.

You will find accessories and spare parts on pages 128-130.

You will find information on the HSK standard and fitting dimensions, as well as on the shank position and position of the slots in the section "Technical appendix".

HSK-T turning holders

DDJN... | PDJN...




Turning holders DDJNR | DDJNL 55°/93°

Negative indexable insert



Nominal size HSK-T	Dimensions			Direction of rotation	Insert	Specification	Order No.
	f	d ₁ min	l ₁				
40	27	-	57	R	DN..1506..	MTH-HSK-T040-DDJNR-057-27-15	30335770
40	27	-	57	L	DN..1506..	MTH-HSK-T040-DDJNL-057-27-15	30335771
63	45	-	70	R	DN..1506..	MTH-HSK-T63-DDJNR-075-45-15	30609522
63	45	-	70	L	DN..1506..	MTH-HSK-T63-DDJNL-075-45-15	30609523
100	63	-	100	R	DN..1506..	MTH-HSK-T100-DDJNR-100-63-15	30609524
100	63	-	100	L	DN..1506..	MTH-HSK-T100-DDJNL-100-63-15	30609525



Turning holders PDJNR | PDJNL 55°/93°

Negative indexable insert



Nominal size HSK-T	Dimensions			Direction of rotation	Insert	Specification	Order No.
	f	d ₁ min	l ₁				
40	27	-	57	R	DN..1506..	MTH-HSK-T040-PDJNR-057-27-15	30335772
40	27	-	57	L	DN..1506..	MTH-HSK-T040-PDJNL-057-27-15	30335773
63	45	-	70	R	DN..1506..	MTH-HSK-T063-PDJNR-070-45-15	30609526
63	45	-	70	L	DN..1506..	MTH-HSK-T063-PDJNL-070-45-15	30609527
100	63	-	100	R	DN..1506..	MTH-HSK-T100-PDJNR-100-63-15	30609528
100	63	-	100	L	DN..1506..	MTH-HSK-T100-PDJNL-100-63-15	30609529


Dimensions in mm.

You will find accessories and spare parts on pages 128-130.

You will find information on the HSK standard and fitting dimensions, as well as on the shank position and position of the slots in the section "Technical appendix".

HSK-T turning holders

DDNNN | PDNNN




Turning holders DDNNN 62.5°/55°/62.5°

Negative indexable insert



Nominal size HSK-T	Dimensions			Direction of rotation	Insert	Specification	Order No.
	f	d ₁ min	l ₁				
40	-	-	80	N	DN..1506..	MTH-HSK-T040-DDNNN-080-00-15	30335782
63	-	-	100	N	DN.. 1506..	MTH-HSK-T063-DDNNN-100-00-15	30609530
63	-	-	130	N	DN.. 1506..	MTH-HSK-T063-DDNNN-130-00-15	30609531
100	-	-	125	N	DN.. 1506..	MTH-HSK-T100-DDNNN-125-00-15	30609532



Turning holders PDNNN 62.5°/55°/62.5°

Negative indexable insert



Nominal size HSK-T	Dimensions			Direction of rotation	Insert	Specification	Order No.
	f	d ₁ min	l ₁				
40	-	-	80	N	DN..1506..	MTH-HSK-T040-PDNNN-080-00-15	30335783
63	-	-	100	N	DN.. 1506..	MTH-HSK-T063-PDNNN-100-00-15	30609533
63	-	-	130	N	DN.. 1506..	MTH-HSK-T063-PDNNN-130-00-15	30609534
100	-	-	125	N	DN.. 1506..	MTH-HSK-T100-PDNNN-125-00-15	30609535


Dimensions in mm.

You will find accessories and spare parts on pages 128-130.

You will find information on the HSK standard and fitting dimensions, as well as on the shank position and position of the slots in the section "Technical appendix".

HSK-T turning holders

DDUN... | PDUN...




Turning holders DDUNR | DDUNL 93°/55°

Negative indexable insert



Nominal size HSK-T	Dimensions			Direction of rotation	Insert	Specification	Order No.
	f	d ₁ min	l ₁				
40	27	50	55	R	DN..1506..	MTH-HSK-T040-DDUNR-055-27-15	30335764
40	27	50	55	L	DN..1506..	MTH-HSK-T040-DDUNL-055-27-15	30335765
63	45	80	70	R	DN..1506..	MTH-HSK-T063-DDUNR-070-45-15	30609536
63	45	80	70	L	DN..1506..	MTH-HSK-T063-DDUNL-070-45-15	30609537
100	63	120	100	R	DN..1506..	MTH-HSK-T100-DDUNR-100-63-15	30609538
100	63	120	100	L	DN..1506..	MTH-HSK-T100-DDUNL-100-63-15	30609539



Turning holders PDUNR | PDUNL 93°/55°

Negative indexable insert



Nominal size HSK-T	Dimensions			Direction of rotation	Insert	Specification	Order No.
	f	d ₁ min	l ₁				
40	27	50	55	R	DN..1506..	MTH-HSK-T040-PDUNR-055-27-15	30335766
40	27	50	55	L	DN..1506..	MTH-HSK-T040-PDUNL-055-27-15	30335767
63	45	80	70	R	DN..1506..	MTH-HSK-T063-PDUNR-070-45-15	30609540
63	45	80	70	L	DN..1506..	MTH-HSK-T063-PDUNL-070-45-15	30609541
100	63	120	100	R	DN..1506..	MTH-HSK-T100-PDUNR-100-63-15	30609542
100	63	120	100	L	DN..1506..	MTH-HSK-T100-PDUNL-100-63-15	30609543


Dimensions in mm.

You will find accessories and spare parts on pages 128-130.

You will find information on the HSK standard and fitting dimensions, as well as on the shank position and position of the slots in the section "Technical appendix".

HSK-T turning holders

DSBN... | PSBN...




Turning holders DSBNR | DSBNL 90°/75°

Negative indexable insert



Nominal size HSK-T	Dimensions			Direction of rotation	Insert	Specification	Order No.
	f	d ₁ min	l ₁				
40	27	-	55	R	SN.. 1204..	MTH-HSK-T040-DSBNR-055-27-12	30609544
40	27	-	55	L	SN.. 1204..	MTH-HSK-T040-DSBNL-055-27-12	30609545
63	45	-	70	R	SN.. 1204..	MTH-HSK-T063-DSBNR-070-45-12	30609546
63	45	-	70	L	SN.. 1204..	MTH-HSK-T063-DSBNL-070-45-12	30609547
100	63	-	100	R	SN.. 1204..	MTH-HSK-T100-DSBNR-100-63-12	30609548
100	63	-	100	L	SN.. 1204..	MTH-HSK-T100-DSBNL-100-63-12	30609549



Turning holders PSBNR | PSBNL 90°/75°

Negative indexable insert



Nominal size HSK-T	Dimensions			Direction of rotation	Insert	Specification	Order No.
	f	d ₁ min	l ₁				
40	27	-	55	R	SN.. 1204..	MTH-HSK-T040-PSBNR-055-27-12	30609550
40	27	-	55	L	SN.. 1204..	MTH-HSK-T040-PSBNL-055-27-12	30609551
63	45	-	70	R	SN.. 1204..	MTH-HSK-T063-PSBNR-070-45-12	30609552
63	45	-	70	L	SN.. 1204..	MTH-HSK-T063-PSBNL-070-45-12	30609553
100	63	-	100	R	SN.. 1204..	MTH-HSK-T100-PSBNR-100-63-12	30609554
100	63	-	100	L	SN.. 1204..	MTH-HSK-T100-PSBNL-100-63-12	30609555


Dimensions in mm.

You will find accessories and spare parts on pages 128-130.

You will find information on the HSK standard and fitting dimensions, as well as on the shank position and position of the slots in the section "Technical appendix".

HSK-T turning holders

DSSN... | PSSN...




Turning holders DSSNR | DSSNL 45°/90°

Negative indexable insert



Nominal size HSK-T	Dimensions			Direction of rotation	Insert	Specification	Order No.
	f	d ₁ min	l ₁				
40	27	-	55	R	SN.. 1204..	MTH-HSK-T040-DSSNR-055-27-12	30609556
40	27	-	55	L	SN.. 1204..	MTH-HSK-T040-DSSNL-055-27-12	30609557
63	45	-	70	R	SN.. 1204..	MTH-HSK-T063-DSSNR-070-45-12	30609558
63	45	-	70	L	SN.. 1204..	MTH-HSK-T063-DSSNL-070-45-12	30609559
100	63	-	100	R	SN.. 1204..	MTH-HSK-T100-DSSNR-100-63-12	30609560
100	63	-	100	L	SN.. 1204..	MTH-HSK-T100-DSSNL-100-63-12	30609561



Turning holders PSSNR | PSSNL 45°/90°

Negative indexable insert



Nominal size HSK-T	Dimensions			Direction of rotation	Insert	Specification	Order No.
	f	d ₁ min	l ₁				
40	27	-	55	R	SN.. 1204..	MTH-HSK-T040-PSSNR-055-27-12	30609562
40	27	-	55	L	SN.. 1204..	MTH-HSK-T040-PSSNL-055-27-12	30609563
63	45	-	70	R	SN.. 1204..	MTH-HSK-T063-PSSNR-070-45-12	30609564
63	45	-	70	L	SN.. 1204..	MTH-HSK-T063-PSSNL-070-45-12	30609565
100	63	-	100	R	SN.. 1204..	MTH-HSK-T100-PSSNR-100-63-12	30609566
100	63	-	100	L	SN.. 1204..	MTH-HSK-T100-PSSNL-100-63-12	30609567


Dimensions in mm.

You will find accessories and spare parts on pages 128-130.

You will find information on the HSK standard and fitting dimensions, as well as on the shank position and position of the slots in the section "Technical appendix".

HSK-T turning holders

DVPN... | DVUN...




Turning holders DVPNR | DVPNL 117.5°/35°

Negative indexable insert



Nominal size HSK-T	Dimensions			Direction of rotation	Insert	Specification	Order No.
	f	d ₁ min	l ₁				
40	27	-	55	R	VN..1604..	MTH-HSK-T040-DVPNR-055-27-16	30335776
40	27	-	55	L	VN..1604..	MTH-HSK-T040-DVPNL-055-27-16	30335777
63	45	80	70	R	VN..1604..	MTH-HSK-T063-DVPNR-070-45-16	30609568
63	45	80	70	L	VN..1604..	MTH-HSK-T063-DVPNL-070-45-16	30609569
100	63	120	100	R	VN..1604..	MTH-HSK-T100-DVPNR-100-63-16	30609570
100	63	120	100	L	VN..1604..	MTH-HSK-T100-DVPNL-100-63-16	30609571



Turning holders DVUNR | DVUNL 93°/35°

Negative indexable insert



Nominal size HSK-T	Dimensions			Direction of rotation	Insert	Specification	Order No.
	f	d ₁ min	l ₁				
40	27	-	55	R	VN..1604..	MTH-HSK-T040-DVUNR-055-27-16	30335760
40	27	-	55	L	VN..1604..	MTH-HSK-T040-DVUNL-055-27-16	30335761
63	45	80	70	R	VN..1604..	MTH-HSK-T063-DVUNR-070-45-16	30609572
63	45	80	70	L	VN..1604..	MTH-HSK-T063-DVUNL-070-45-16	30609573
100	63	120	100	R	VN..1604..	MTH-HSK-T100-DVUNR-100-63-16	30609574
100	63	120	100	L	VN..1604..	MTH-HSK-T100-DVUNL-100-63-16	30609575


Dimensions in mm.

You will find accessories and spare parts on pages 128-130.

You will find information on the HSK standard and fitting dimensions, as well as on the shank position and position of the slots in the section "Technical appendix".

HSK-T turning holders

DVVNN | DVJN...




Turning holders DVVNN 72.5°/35°/72.5°

Negative indexable insert



Nominal size HSK-T	Dimensions			Direction of rotation	Insert	Specification	Order No.
	f	d ₁ min	l ₁				
40	-	-	80	N	VN..1604..	MTH-HSK-T040-DVVNN-080-00-16	30335785
63	-	-	100	N	VN..1604..	MTH-HSK-T063-DVVNN-100-00-16	30609576
63	-	-	130	N	VN..1604..	MTH-HSK-T063-DVVNN-130-00-16	30609577
100	-	-	125	N	VN..1604..	MTH-HSK-T100-DVVNN-125-00-16	30609578



View: right design

Turning holders DVJNR | DVJNL 93°/35°

Negative indexable insert



Nominal size HSK-T	Dimensions			Direction of rotation	Insert	Specification	Order No.
	f	d ₁ min	l ₁				
100	63	-	100	R	VN..1604..	MTH-HSK-T100-DVJNR-100-63-16	30609579
100	63	-	100	L	VN..1604..	MTH-HSK-T100-DVJNL-100-63-16	30609580


Dimensions in mm.

You will find accessories and spare parts on pages 128-130.

You will find information on the HSK standard and fitting dimensions, as well as on the shank position and position of the slots in the section "Technical appendix".

HSK-T turning holders

DWLN... | PWLN...



Turning holders DWLNR | DWLNL 95°/80°

Negative indexable insert



Nominal size HSK-T	Dimensions			Direction of rotation	Insert	Specification	Order No.
	f	d ₁ min	l ₁				
40	27	50	55	R	WN..0804..	MTH-HSK-T040-DWLNR-055-27-08	30609581
40	27	50	55	L	WN..0804..	MTH-HSK-T040-DWLNL-055-27-08	30609582
63	45	80	70	R	WN..0804..	MTH-HSK-T063-DWLNR-070-45-08	30609583
63	45	80	70	L	WN..0804..	MTH-HSK-T063-DWLNL-070-45-08	30609584
100	63	120	100	R	WN..0804..	MTH-HSK-T100-DWLNR-100-63-08	30609586
100	63	120	100	L	WN..0804..	MTH-HSK-T100-DWLNL-100-63-08	30609585

Turning holders PWLNR | PWLNL 95°/80°

Negative indexable insert



Nominal size HSK-T	Dimensions			Direction of rotation	Insert	Specification	Order No.
	f	d ₁ min	l ₁				
40	27	50	55	R	WN..0804..	MTH-HSK-T040-PWLNR-055-27-08	30609587
40	27	50	55	L	WN..0804..	MTH-HSK-T040-PWLNL-055-27-08	30609588
63	45	80	70	R	WN..0804..	MTH-HSK-T063-PWLNR-070-45-08	30609589
63	45	80	70	L	WN..0804..	MTH-HSK-T063-PWLNL-070-45-08	30609590
100	63	120	100	R	WN..0804..	MTH-HSK-T100-PWLNR-100-63-08	30609591
100	63	120	100	L	WN..0804..	MTH-HSK-T100-PWLNL-100-63-08	30609592


Dimensions in mm.

You will find accessories and spare parts on pages 128-130.

You will find information on the HSK standard and fitting dimensions, as well as on the shank position and position of the slots in the section "Technical appendix".

HSK-T turning holders, long

DCLN...



Turning holders DCLNR | DCLNL 95°/80°

Negative indexable insert



Nominal size HSK-T	Dimensions				Direction of rotation	Insert	Specification	Order No.
	f	d ₁ min	l ₁	l ₂				
63	27	50	140	114	R	CN.. 1204..	MTH-HSK-T063-DCLNR-140-27-12	30609661
63	27	50	140	114	L	CN.. 1204..	MTH-HSK-T063-DCLNL-140-27-12	30609662
63	27	50	180	154	R	CN.. 1204..	MTH-HSK-T063-DCLNR-180-27-12	30609663
63	27	50	180	154	L	CN.. 1204..	MTH-HSK-T063-DCLNL-180-27-12	30609664
100	27	50	150	121	R	CN.. 1204..	MTH-HSK-T100-DCLNR-150-27-12	30609665
100	27	50	150	121	L	CN.. 1204..	MTH-HSK-T100-DCLNL-150-27-12	30609666
100	27	50	200	171	R	CN.. 1204..	MTH-HSK-T100-DCLNR-200-27-12	30609667
100	27	50	200	171	L	CN.. 1204..	MTH-HSK-T100-DCLNL-200-27-12	30609668
100	35	63	150	121	R	CN.. 1204..	MTH-HSK-T100-DCLNR-150-35-12	30609669
100	35	63	150	121	L	CN.. 1204..	MTH-HSK-T100-DCLNL-150-35-12	30609670
100	35	63	200	171	R	CN.. 1204..	MTH-HSK-T100-DCLNR-200-35-12	30609671
100	35	63	200	171	L	CN.. 1204..	MTH-HSK-T100-DCLNL-200-35-12	30609672


Dimensions in mm.

You will find accessories and spare parts on pages 128-130.

You will find information on the HSK standard and fitting dimensions, as well as on the shank position and position of the slots in the section "Technical appendix".

HSK-T turning holders, long

PCLN...



Turning holders PCLNR | PCLNL 95°/80°

Negative indexable insert



Nominal size HSK-T	Dimensions				Direction of rotation	Insert	Specification	Order No.
	f	$d_1 \text{ min}$	l_1	l_2				
63	27	50	140	114	R	CN.. 1204..	MTH-HSK-T063-PCLNR-140-27-12	30609673
63	27	50	140	114	L	CN.. 1204..	MTH-HSK-T063-PCLNL-140-27-12	30609674
63	27	50	180	154	R	CN.. 1204..	MTH-HSK-T063-PCLNR-180-27-12	30609675
63	27	50	180	154	L	CN.. 1204..	MTH-HSK-T063-PCLNL-180-27-12	30609676
100	27	50	150	121	R	CN.. 1204..	MTH-HSK-T100-PCLNR-150-27-12	30609677
100	27	50	150	121	L	CN.. 1204..	MTH-HSK-T100-PCLNL-150-27-12	30609678
100	27	50	200	171	R	CN.. 1204..	MTH-HSK-T100-PCLNR-200-27-12	30609679
100	27	50	200	171	L	CN.. 1204..	MTH-HSK-T100-PCLNL-200-27-12	30609680
100	35	63	150	121	R	CN.. 1204..	MTH-HSK-T100-PCLNR-150-35-12	30609681
100	35	63	150	121	L	CN.. 1204..	MTH-HSK-T100-PCLNL-150-35-12	30609682
100	35	63	200	171	R	CN.. 1204..	MTH-HSK-T100-PCLNR-200-35-12	30609683
100	35	63	200	171	L	CN.. 1204..	MTH-HSK-T100-PCLNL-200-35-12	30609684


Dimensions in mm.

You will find accessories and spare parts on pages 128-130.

You will find information on the HSK standard and fitting dimensions, as well as on the shank position and position of the slots in the section "Technical appendix".

HSK-T turning holders, long

DDQN...



Turning holders DDQNR | DDQNL 107.5°/55°

Negative indexable insert



Nominal size HSK-T	Dimensions				Direction of rotation	Insert	Specification	Order No.
	f	d ₁ min	l ₁	l ₂				
63	27	50	140	114	R	DN.. 1506..	MTH-HSK-T063-DDQNR-140-27-15	30609685
63	27	50	140	114	L	DN.. 1506..	MTH-HSK-T063-DDQNL-140-27-15	30609686
63	27	50	180	154	R	DN.. 1506..	MTH-HSK-T063-DDQNR-180-27-15	30609687
63	27	50	180	154	L	DN.. 1506..	MTH-HSK-T063-DDQNL-180-27-15	30609688
100	27	50	150	121	R	DN.. 1506..	MTH-HSK-T100-DDQNR-150-27-15	30609689
100	27	50	150	121	L	DN.. 1506..	MTH-HSK-T100-DDQNL-150-27-15	30609690
100	27	50	200	171	R	DN.. 1506..	MTH-HSK-T100-DDQNR-200-27-15	30609691
100	27	50	200	171	L	DN.. 1506..	MTH-HSK-T100-DDQNL-200-27-15	30609692
100	35	63	150	121	R	DN.. 1506..	MTH-HSK-T100-DDQNR-150-35-15	30609693
100	35	63	150	121	L	DN.. 1506..	MTH-HSK-T100-DDQNL-150-35-15	30609694
100	35	63	200	171	R	DN.. 1506..	MTH-HSK-T100-DDQNR-200-35-15	30609695
100	35	63	200	171	L	DN.. 1506..	MTH-HSK-T100-DDQNL-200-35-15	30609696


Dimensions in mm.

You will find accessories and spare parts on pages 128-130.

You will find information on the HSK standard and fitting dimensions, as well as on the shank position and position of the slots in the section "Technical appendix".

HSK-T turning holders, long

PDQN...



Turning holders PDQNR | PDQNL 107.5°/55°

Negative indexable insert



Nominal size HSK-T	Dimensions				Direction of rotation	Insert	Specification	Order No.
	f	d ₁ min	l ₁	l ₂				
63	27	50	140	114	R	DN.. 1506..	MTH-HSK-T063-PDQNR-140-27-15	30609697
63	27	50	140	114	L	DN.. 1506..	MTH-HSK-T063-PDQNL-140-27-15	30609698
63	27	50	180	154	R	DN.. 1506..	MTH-HSK-T063-PDQNR-180-27-15	30609699
63	27	50	180	154	L	DN.. 1506..	MTH-HSK-T063-PDQNL-180-27-15	30609700
100	27	50	150	121	R	DN.. 1506..	MTH-HSK-T100-PDQNR-150-27-15	30609701
100	27	50	150	121	L	DN.. 1506..	MTH-HSK-T100-PDQNL-150-27-15	30609702
100	27	50	200	171	R	DN.. 1506..	MTH-HSK-T100-PDQNR-200-27-15	30609703
100	27	50	200	171	L	DN.. 1506..	MTH-HSK-T100-PDQNL-200-27-15	30609704
100	35	63	150	121	R	DN.. 1506..	MTH-HSK-T100-PDQNR-150-35-15	30609705
100	35	63	150	121	L	DN.. 1506..	MTH-HSK-T100-PDQNL-150-35-15	30609706
100	35	63	200	171	R	DN.. 1506..	MTH-HSK-T100-PDQNR-200-35-15	30609707
100	35	63	200	171	L	DN.. 1506..	MTH-HSK-T100-PDQNL-200-35-15	30609708


Dimensions in mm.

You will find accessories and spare parts on pages 128-130.

You will find information on the HSK standard and fitting dimensions, as well as on the shank position and position of the slots in the section "Technical appendix".

HSK-T turning holders

SCLC... | SCMCN




Turning holders SCLCR | SCLCL 95°/80°

Positive indexable insert



Nominal size HSK-T	Dimensions			Direction of rotation	Insert	Specification	Order No.
	f	d ₁ min	l ₁				
40	27	50	55	R	CC..1204..	MTH-HSK-T040-SCLCR-055-27-12	30335746
40	27	50	55	L	CC..1204..	MTH-HSK-T040-SCLCL-055-27-12	30335747
63	45	80	70	R	CC..1204..	MTH-HSK-T063-SCLCR-070-45-12	30609593
63	45	80	70	L	CC..1204..	MTH-HSK-T063-SCLCL-070-45-12	30609594
100	63	120	100	R	CC..1204..	MTH-HSK-T100-SCLCR-100-63-12	30609595
100	63	120	100	L	CC..1204..	MTH-HSK-T100-SCLCL-100-63-12	30609596



Turning holders SCMCN 50°/80°/50°

Positive indexable insert



Nominal size HSK-T	Dimensions			Direction of rotation	Insert	Specification	Order No.
	f	d ₁ min	l ₁				
40	-	-	80	N	CC..1204..	MTH-HSK-T040-SCMCN-080-00-12	30335778
63	-	-	100	N	CC..1204..	MTH-HSK-T063-SCMCN-100-00-12	30609597
63	-	-	130	N	CC..1204..	MTH-HSK-T063-SCMCN-130-00-12	30609598
100	-	-	125	N	CC..1204..	MTH-HSK-T100-SCMCN-125-00-12	30609599


Dimensions in mm.

You will find accessories and spare parts on pages 128-130.

You will find information on the HSK standard and fitting dimensions, as well as on the shank position and position of the slots in the section "Technical appendix".

HSK-T turning holders

SDHC... | SDNCN



Turning holders SDHCR | SDHCL 107.5°/55°

Positive indexable insert



Nominal size HSK-T	Dimensions			Direction of rotation	Insert	Specification	Order No.
	f	d ₁ min	l ₁				
40	27	50	55	R	DC..11 T3..	MTH-HSK-T040-SDHCR-055-27-11	30335752
40	27	50	55	L	DC..11 T3..	MTH-HSK-T040-SDHCL-055-27-11	30335753
63	45	80	70	R	DC..11 T3..	MTH-HSK-T063-SDHCR-070-45-11	30609600
63	45	80	70	L	DC..11 T3..	MTH-HSK-T063-SDHCL-070-45-11	30609601
100	63	120	100	R	DC..11 T3..	MTH-HSK-T100-SDHCR-100-63-11	30609602
100	63	120	100	L	DC..11 T3..	MTH-HSK-T100-SDHCL-100-63-11	30609603

Turning holders SDNCN 62.5°/55°/62.5°

Positive indexable insert



Nominal size HSK-T	Dimensions			Direction of rotation	Insert	Specification	Order No.
	f	d ₁ min	l ₁				
40	-	-	80	N	DC..11 T3..	MTH-HSK-T040-SDNCN-080-00-11	30335781
63	-	-	100	N	DC..11 T3..	MTH-HSK-T063-SDNCN-100-00-11	30609604
63	-	-	130	N	DC..11 T3..	MTH-HSK-T063-SDNCN-130-00-11	30609605
100	-	-	125	N	DC..11 T3..	MTH-HSK-T100-SDNCN-125-00-11	30609606


Dimensions in mm.

You will find accessories and spare parts on pages 128-130.

You will find information on the HSK standard and fitting dimensions, as well as on the shank position and position of the slots in the section "Technical appendix".

HSK-T turning holders

SDJC... | SDUC...




Turning holders SDJCR | SDJCL 93°/55°

Positive indexable insert



Nominal size HSK-T	Dimensions			Direction of rotation	Insert	Specification	Order No.
	f	d ₁ min	l ₁				
40	27	50	55	R	DC..11 T3..	MTH-HSK-T040-SDJCR-055-27-11	30335768
40	27	50	55	L	DC..11 T3..	MTH-HSK-T040-SDJCL-055-27-11	30335769
63	45	80	70	R	DC..11T3..	MTH-HSK-T063-SDJCR-070-45-11	30609611
63	45	80	70	L	DC..11T3..	MTH-HSK-T063-SDJCL-070-45-11	30609612
100	63	120	100	R	DC..11T3..	MTH-HSK-T100-SDJCR-100-63-11	30609613
100	63	120	100	L	DC..11T3..	MTH-HSK-T100-SDJCL-100-63-11	30609614



Turning holders SDUCR | SDUCL 93°/55°

Positive indexable insert



Nominal size HSK-T	Dimensions			Direction of rotation	Insert	Specification	Order No.
	f	d ₁ min	l ₁				
40	27	50	55	R	DC..11 T3..	MTH-HSK-T040-SDUCR-055-27-11	30335762
40	27	50	55	L	DC..11 T3..	MTH-HSK-T040-SDUCL-055-27-11	30335763
63	45	80	70	R	DC..11 T3..	MTH-HSK-T063-SDUCR-070-45-11	30609607
63	45	80	70	L	DC..11 T3..	MTH-HSK-T063-SDUCL-070-45-11	30609608
100	63	120	100	R	DC..11 T3..	MTH-HSK-T100-SDUCR-100-63-11	30609609
100	63	120	100	L	DC..11 T3..	MTH-HSK-T100-SDUCL-100-63-11	30609610


Dimensions in mm.

You will find accessories and spare parts on pages 128-130.

You will find information on the HSK standard and fitting dimensions, as well as on the shank position and position of the slots in the section "Technical appendix".

HSK-T turning holders

SSBC... | SSSC...




Turning holders SSBCR | SBCL 75°/90°

Positive indexable insert



Nominal size HSK-T	Dimensions			Direction of rotation	Insert	Specification	Order No.
	f	d ₁ min	l ₁				
40	27	-	55	R	SC.. 1204..	MTH-HSK-T040-SSBCR-055-27-12	30609615
40	27	-	55	L	SC.. 1204..	MTH-HSK-T040-SBCL-055-27-12	30609616
63	45	-	70	R	SC.. 1204..	MTH-HSK-T063-SSBCR-070-45-12	30609617
63	45	-	70	L	SC.. 1204..	MTH-HSK-T063-SBCL-070-45-12	30609618
100	63	-	100	R	SC.. 1204..	MTH-HSK-T100-SSBCR-100-63-12	30609619
100	63	-	100	L	SC.. 1204..	MTH-HSK-T100-SBCL-100-63-12	30609620



Turning holders SSSCR | SSCL 45°/90°

Positive indexable insert



Nominal size HSK-T	Dimensions			Direction of rotation	Insert	Specification	Order No.
	f	d ₁ min	l ₁				
40	27	-	55	R	SC.. 1204..	MTH-HSK-T040-SSSCR-055-27-12	30609621
40	27	-	55	L	SC.. 1204..	MTH-HSK-T040-SSCL-055-27-12	30609622
63	45	-	70	R	SC.. 1204..	MTH-HSK-T063-SSSCR-070-45-12	30609623
63	45	-	70	L	SC.. 1204..	MTH-HSK-T063-SSCL-070-45-12	30609624
100	63	-	100	R	SC.. 1204..	MTH-HSK-T100-SSSCR-100-63-12	30609625
100	63	-	100	L	SC.. 1204..	MTH-HSK-T100-SSCL-100-63-12	30609626


Dimensions in mm.

You will find accessories and spare parts on pages 128-130.

You will find information on the HSK standard and fitting dimensions, as well as on the shank position and position of the slots in the section "Technical appendix".

HSK-T turning holders

SVPB... | SVPC...



Turning holders SVPBR | SVPBL | SVPCR | SVPCL 117.5°/35°

Positive indexable insert



Nominal size HSK-T	Dimensions			Direction of rotation	Insert	Specification	Order No.
	f	d ₁ min	l ₁				
40	27	50	55	R	VB..1604..	MTH-HSK-T040-SVPBR-055-27-16	30609635
40	27	50	55	L	VB..1604..	MTH-HSK-T040-SVPBL-055-27-16	30609636
40	27	50	55	R	VC..1604..	MTH-HSK-T040-SVPCR-055-27-16	30335774
40	27	50	55	L	VC..1604..	MTH-HSK-T040-SVPCL-055-27-16	30335775
63	45	80	70	R	VB..1604..	MTH-HSK-T063-SVPBR-070-45-16	30609637
63	45	80	70	L	VB..1604..	MTH-HSK-T063-SVPBL-070-45-16	30609638
63	45	80	70	R	VC..1604..	MTH-HSK-T063-SVPCR-070-45-16	30609639
63	45	80	70	L	VC..1604..	MTH-HSK-T063-SVPCL-070-45-16	30609640
100	63	120	100	R	VB..1604..	MTH-HSK-T100-SVPBR-100-63-16	30609641
100	63	120	100	L	VB..1604..	MTH-HSK-T100-SVPBL-100-63-16	30609642
100	63	120	100	R	VC..1604..	MTH-HSK-T100-SVPCR-100-63-16	30609643
100	63	120	100	L	VC..1604..	MTH-HSK-T100-SVPCL-100-63-16	30609644


Dimensions in mm.

You will find accessories and spare parts on pages 128-130.

You will find information on the HSK standard and fitting dimensions, as well as on the shank position and position of the slots in the section "Technical appendix".

HSK-T turning holders

SVUB... | SVUC...



Turning holders SVUBR | SVUBL | SVUCR | SVUCL 93°/35°

Positive indexable insert

Nominal size HSK-T	Dimensions			Direction of rotation	Insert	Specification	Order No.
	f	d ₁ min	l ₁				
40	27	50	55	R	VB..1604..	MTH-HSK-T040-SVUBR-055-27-12	30609645
40	27	50	55	L	VB..1604..	MTH-HSK-T040-SVUBL-055-27-12	30609646
40	27	50	55	R	VC..1604..	MTH-HSK-T040-SVUCR-055-27-12	30335758
40	27	50	55	L	VC..1604..	MTH-HSK-T040-SVUCL-055-27-12	30335759
63	45	80	70	R	VB..1604..	MTH-HSK-T063-SVUBR-070-45-12	30609647
63	45	80	70	L	VB..1604..	MTH-HSK-T063-SVUBL-070-45-12	30609648
63	45	80	70	R	VC..1604..	MTH-HSK-T063-SVUCR-070-45-12	30609649
63	45	80	70	L	VC..1604..	MTH-HSK-T063-SVUCL-070-45-12	30609650
100	63	120	100	R	VB..1604..	MTH-HSK-T100-SVUBR-100-63-12	30609651
100	63	120	100	L	VB..1604..	MTH-HSK-T100-SVUBL-100-63-12	30609652
100	63	120	100	R	VC..1604..	MTH-HSK-T100-SVUCR-100-63-12	30609653
100	63	120	100	L	VC..1604..	MTH-HSK-T100-SVUCL-100-63-12	30609654


Dimensions in mm.

You will find accessories and spare parts on pages 128-130.

You will find information on the HSK standard and fitting dimensions, as well as on the shank position and position of the slots in the section "Technical appendix".

HSK-T turning holders

SVBNN | SWCN | SVJB... | SVJC...




Turning holders SVBNN | SWCN 72.5°/35°/72.5°

Positive indexable insert



Nominal size HSK-T	Dimensions			Direction of rotation	Insert	Specification	Order No.
	f	d ₁ min	l ₁				
40	-	-	80	N	VB..1604..	MTH-HSK-T040-SVBN-080-00-16	30609655
40	-	-	80	N	VC..1604..	MTH-HSK-T040-SWCN-080-00-16	30335784
63	-	-	100	N	VB..1604..	MTH-HSK-T063-SVBN-100-00-16	30609656
63	-	-	130	N	VB..1604..	MTH-HSK-T063-SVBN-130-00-16	30609657
63	-	-	100	N	VC..1604..	MTH-HSK-T063-SWCN-100-00-16	30606133
63	-	-	130	N	VC..1604..	MTH-HSK-T063-SWCN-130-00-16	30609658
100	-	-	125	N	VB..1604..	MTH-HSK-T100-SVBN-125-00-16	30609659
100	-	-	125	N	VC..1604..	MTH-HSK-T100-SWCN-125-00-16	30609660



Turning holders SVJBR | SVJBL | SVJCR | SVJCL 93°/35°

Positive indexable insert



Nominal size HSK-T	Dimensions			Direction of rotation	Insert	Specification	Order No.
	f	d ₁ min	l ₁				
63	45	80	71,5	R	VB..1604..	MTH-HSK-T063-SVJBR-072-45-16	30609627
63	45	80	71,5	L	VB..1604..	MTH-HSK-T063-SVJBL-072-45-16	30609628
63	45	80	71,5	R	VC..1604..	MTH-HSK-T063-SVJCR-072-45-16	30609629
63	45	80	71,5	L	VC..1604..	MTH-HSK-T063-SVJCL-072-45-16	30609630
100	63	120	100	R	VB..1604..	MTH-HSK-T100-SVJBR-100-63-16	30609631
100	63	120	100	L	VB..1604..	MTH-HSK-T100-SVJBL-100-63-16	30609632
100	63	120	100	R	VC..1604..	MTH-HSK-T100-SVJCR-100-63-16	30609633
100	63	120	100	L	VC..1604..	MTH-HSK-T100-SVJCL-100-63-16	30609634


Dimensions in mm.

You will find accessories and spare parts on pages 128-130.

You will find information on the HSK standard and fitting dimensions, as well as on the shank position and position of the slots in the section "Technical appendix".

HSK-T turning holders, long

SCLCR | SCLCL



Turning holders SCLCR | SCLCL 95°/80°

Positive indexable insert



Nominal size HSK-T	Dimensions				Direction of rotation	Insert	Specification	Order No.
	f	$d_1 \text{ min}$	l_1	l_2				
40	17	32	110	90	R	CC..1204..	MTH-HSK-T040-SCLCR-110-17-12	30270295
40	17	32	110	90	L	CC..1204..	MTH-HSK-T040-SCLCL-110-17-12	30461609
40	17	32	140	120	R	CC..1204..	MTH-HSK-T040-SCLCR-140-17-12	30461611
40	17	32	140	120	L	CC..1204..	MTH-HSK-T040-SCLCL-140-17-12	30461615
63	22	40	125	99	R	CC..1204..	MTH-HSK-T063-SCLCR-125-22-12	30609709
63	22	40	125	99	L	CC..1204..	MTH-HSK-T063-SCLCL-125-22-12	30609710
63	22	40	160	134	R	CC..1204..	MTH-HSK-T063-SCLCR-160-22-12	30609711
63	22	40	160	134	L	CC..1204..	MTH-HSK-T063-SCLCL-160-22-12	30609712
63	27	50	140	114	R	CC..1204..	MTH-HSK-T063-SCLCR-140-27-12	30609713
63	27	50	140	114	L	CC..1204..	MTH-HSK-T063-SCLCL-140-27-12	30609714
63	27	50	180	154	R	CC..1204..	MTH-HSK-T063-SCLCR-180-27-12	30609715
63	27	50	180	154	L	CC..1204..	MTH-HSK-T063-SCLCL-180-27-12	30609716


Dimensions in mm.

You will find accessories and spare parts on pages 128-130.

You will find information on the HSK standard and fitting dimensions, as well as on the shank position and position of the slots in the section "Technical appendix".

HSK-T turning holders, long

SDQCR | SDQCL



Turning holders SDQCR | SDQCL 107.5°/55°

Positive indexable insert



Nominal size HSK-T	Dimensions				Direction of rotation	Insert	Specification	Order No.
	f	$d_1 \text{ min}$	l_1	l_2				
40	17	32	110	90	R	DC..11T3..	MTH-HSK-T040-SDQCR-110-17-11	30461623
40	17	32	110	90	L	DC..11T3..	MTH-HSK-T040-SDQCL-110-17-11	30461627
40	17	32	140	120	R	DC..11T3..	MTH-HSK-T040-SDQCR-140-17-11	30461629
40	17	32	140	120	L	DC..11T3..	MTH-HSK-T040-SDQCL-140-17-11	30461631
63	22	40	125	99	R	DC..11T3..	MTH-HSK-T063-SDQCR-125-22-11	30609717
63	22	40	125	99	L	DC..11T3..	MTH-HSK-T063-SDQCL-125-22-11	30609718
63	22	40	160	134	R	DC..11T3..	MTH-HSK-T063-SDQCR-160-22-11	30609719
63	22	40	160	134	L	DC..11T3..	MTH-HSK-T063-SDQCL-160-22-11	30609720
63	27	50	140	114	R	DC..11T3..	MTH-HSK-T063-SDQCR-140-27-11	30609721
63	27	50	140	114	L	DC..11T3..	MTH-HSK-T063-SDQCL-140-27-11	30609722
63	27	50	180	154	R	DC..11T3..	MTH-HSK-T063-SDQCR-180-27-11	30609723
63	27	50	180	154	L	DC..11T3..	MTH-HSK-T063-SDQCL-180-27-11	30609724


Dimensions in mm.

You will find accessories and spare parts on pages 128-130.

You will find information on the HSK standard and fitting dimensions, as well as on the shank position and position of the slots in the section "Technical appendix".

HSK-T shank holders, axial


SH... | SH2R00



Shank holders SHR | SHL

For square connections, axial

Nominal size HSK-T	Dimensions				Direction of rotation	Specification	Order No.
	l_1	l_2	f	Square			
40	80	45	30	20x20	R	MTH-HSK-T040-SHR00-2020	30416653
40	80	45	30	20x20	L	MTH-HSK-T040-SHL00-2020	30416654
63	90	45	30	20x20	R	MTH-HSK-T063-SHR00-2020	30610264
63	90	45	30	20x20	L	MTH-HSK-T063-SHL00-2020	30610265
63	100	58	40	25x25	R	MTH-HSK-T063-SHR00-2525	30610266
63	100	58	40	25x25	L	MTH-HSK-T063-SHL00-2525	30610267
100	125	80	50	25x25	R	MTH-HSK-T100-SHR00-2525	30610268
100	125	80	50	25x25	L	MTH-HSK-T100-SHL00-2525	30610269



Shank holders SH2R00

For square connections, axial, double

Nominal size HSK-T	Dimensions				Direction of rotation	Specification	Order No.
	l_1	l_2	f	Square			
40	80	45	30	20x20	R	MTH-HSK-T040-SH2R00-2020	30610270
63	90	45	30	20x20	R	MTH-HSK-T063-SH2R00-2020	30610271
63	100	58	40	25x25	R	MTH-HSK-T063-SH2R00-2525	30610272
100	125	80	50	25x25	R	MTH-HSK-T100-SH2R00-2525	30610273


Dimensions in mm.

You will find accessories and spare parts on pages 128-130.

You will find information on the HSK standard and fitting dimensions, as well as on the shank position and position of the slots in the section "Technical appendix".

HSK-T shank holders, axial

SH3R00 | BH



Shank holders SH3R00

For square connections, axial, triple

Nominal size HSK-T	Dimensions				Direction of rotation	Specification	Order No.
	l_1	l_2	f	Square			
63	90	45	30	20x20	R	MTH-HSK-T063-SH3R00-2020	30610271
63	100	58	40	25x25	R	MTH-HSK-T063-SH3R00-2525	30610272
100	125	80	50	25x25	R	MTH-HSK-T100-SH3R00-2525	30610276


Dimensions in mm.

You will find accessories and spare parts on pages 128-130.

You will find information on the HSK standard and fitting dimensions, as well as on the shank position and position of the slots in the section "Technical appendix".

HSK-T shank holders, radial I diagonal


SHN90 | BH



Shank holders SHN90

For square connections, radial

Nominal size HSK-T	Dimensions				Direction of rotation	Specification	Order No.
	l_1	l_2	f	Square			
40	75	-	30	20x20	N	MTH-HSK-T040-SHN90-2020	30416652
63	90	-	30	20x20	N	MTH-HSK-T063-SHN90-2020	30416648
63	90	-	40	25x25	N	MTH-HSK-T063-SHN90-2525	30610277
100	100	-	50	25x25	N	MTH-HSK-T100-SHN90-2525	30610278



Shank holders SHR45 I SHL45

For square connections, diagonal

Nominal size HSK-T	Dimensions				Direction of rotation	Specification	Order No.
	l_1	l_2	f	Square			
63	100	-	5	20 x20	R	MTH-HSK-T063-SHR45-2020	30610279
63	100	-	5	20x20	L	MTH-HSK-T063-SHL45-2020	30610280
63	100	-	5	25x25	R	MTH-HSK-T063-SHR45-2525	30610281
63	100	-	5	25x25	L	MTH-HSK-T063-SHL45-2525	30610282


Dimensions in mm.

You will find accessories and spare parts on pages 128-130.

You will find information on the HSK standard and fitting dimensions, as well as on the shank position and position of the slots in the section "Technical appendix".

HSK-T shank holders, round

SH3R00 | BH



Shank holders BH
for round connections

Nominal size HSK-T	Dimensions				Specification	Order No.
	d_1	d_2	l_1	l_2		
40	6	34	55	35	MTH-HSK-T040-BH06-055	30416668
40	8	34	55	35	MTH-HSK-T040-BH08-055	30416669
40	10	34	55	35	MTH-HSK-T040-BH10-055	30416670
40	12	36	55	35	MTH-HSK-T040-BH12-055	30416671
40	16	40	70	50	MTH-HSK-T040-BH16-070	30416672
40	20	44	85	65	MTH-HSK-T040-BH20-085	30821786
63	6	34	60	34	MTH-HSK-T063-BH06-060	30610245
63	8	34	60	34	MTH-HSK-T063-BH08-060	30610246
63	10	34	60	34	MTH-HSK-T063-BH10-060	30610247
63	12	36	60	34	MTH-HSK-T063-BH12-060	30610248
63	16	40	75	49	MTH-HSK-T063-BH16-075	30610249
63	20	44	75	49	MTH-HSK-T063-BH20-075	30610250
63	25	50	75	49	MTH-HSK-T063-BH25-075	30610251
63	32	56	90	64	MTH-HSK-T063-BH32-090	30610252
63	40	63	90	64	MTH-HSK-T063-BH40-090	30610253
100	6	34	70	41	MTH-HSK-T100-BH06-070	30610254
100	8	34	70	41	MTH-HSK-T100-BH08-070	30610255
100	10	34	70	41	MTH-HSK-T100-BH10-070	30610256
100	12	36	70	41	MTH-HSK-T100-BH12-070	30610257
100	16	40	85	56	MTH-HSK-T100-BH16-085	30610258
100	20	44	85	56	MTH-HSK-T100-BH20-085	30610260
100	25	50	85	56	MTH-HSK-T100-BH25-085	30610261
100	32	56	100	71	MTH-HSK-T100-BH32-100	30610262
100	40	63	100	71	MTH-HSK-T100-BH40-100	30610263

Dimensions in mm.

You will find accessories and spare parts on pages 128-130.

You will find information on the HSK standard and fitting dimensions, as well as on the shank position and position of the slots in the section "Technical appendix".

Spare parts for turning tools

For turning holders, negative indexable insert (clamping jaw clamping)

Indexable insert	Indexable insert size	Direction of rotation	Backing plate		Clamping screw		Coolant outlet (nozzle ring)		Clamping jaw	
			Description	Order No.	Description	Order No.	Description	Order No.	Description	Order No.
CN..	1204...	R/L, N	CN_1204 ø6.4	30554799	M6x32	30554626	ø14x12	30554787	33x15x11.7	30554632
CN..	1606..	R/L	CN_1606 ø8	30554796	M6x32	30554626	ø14x12	30554787	33x15x11.7	30554632
CN..	1606..	N	CN_1606 ø8	30554796	M6x32	30554626	ø14x12	30554787	38x15x12.1	30554635
DN..	1506..	R/L	DN_1506 ø6.4	30554800	M6x32	30554626	ø14x12	30554787	33x15x11.7	30554632
SN..	1204..	R/L	SN_1204 ø6.4	30554802	M6x32	30554626	ø14x12	30554787	33x15x11.7	30554632
VN..	1604..	R/L	VN_1604 ø4.95	30554805	M6x32	30554626	ø14x12	30554787	33x15x11.7	30554632
VN..	1604..	N	VN_1604 ø4.95	30554805	M6x32	30554626	ø14x12	30554787	38x15x12.1	30554635
WN..	0804..	R/L	WN_0804 ø6.7	30554806	M6x32	30554626	ø14x12	30554787	33x15x11.7	30554632

For turning holders, negative indexable insert (toggle lever clamping)

Indexable insert	Indexable insert size	Direction of rotation	Backing plate		Clamping screw		Toggle lever		Pipe pin	
			Description	Order No.	Description	Order No.	Description	Order No.	Description	Order No.
CN..	1204...	R/L, N	CN_1204 ø6.4	30554799	M8x1x17.3 SW3	30554816	13.5xø4.4x12.8	30554820	ø6.4x5.8	30554831
CN..	1606..	R/L	CN_1606 ø8	30554796	M8x1x20.3 SW3	30554818	16.25xø6x17.5	30554822	ø8x8.7	30554832
CN..	1606..	N	CN_1606 ø8	30554796	M8x1x20.3 SW3	30554818	16.25xø6x17.5	30554822	ø8x8.7	30554832
DN..	1506..	R/L	DN_1506 ø6.4	30554800	M8x1x17.3 SW3	30554816	16.95xø4.7x14.8	30554825	ø6.4x5.8	30554831
DN..	1506..	N	DN_1506 ø6.4	30554800	M8x1x17.3 SW3	30554816	16.95xø4.7x14.8	30554825	ø6.4x5.8	30554831
SN..	1204..	R/L	SN_1204 ø6.4	30554802	M8x1x17.3 SW3	30554816	13.5xø4.4x12.8	30554820	ø6.4x5.8	30554831
WN..	0804..	R/L	WN_0804 ø6.7	30554806	M8x1x17.3 SW3	30554816	16.95xø4.7x14.8	30554825	ø6.4x5.8	30554831

For turning holders, positive indexable insert (screw clamping)

Indexable insert	Indexable insert size	Clamping screw		Torx screwdriver	
		Torx size	Order No.	Description	Order No.
CC..	1204...	20	30554615	T20	10019470
DC..	11T3..	15	30554618	T15	10019469
SC..	1204..	20	30554615	T20	10019470
VB..	-	15	30554618	T15	10019469
VC..	1604..	15	30554618	T15	10019469



For tool holders with round connection

d ₁	Threaded pin in accordance with DIN 4026	
	Description	Order No.
6	M6x10-45H	10003451
8-12	M8x10-45H	10003465
16-20	M10x12-45H	10003945

For tool holders with square connection

Square	Threaded pin in accordance with DIN 4026	
	Description	Order No.
20x20	M10x18-45H	30554621
25x25	M12x25-45H	10003957

Coolant tubes, blanking plugs



Coolant tubes in accordance with DIN 69895

HSK	Dimensions			Order No.
	G	d ₁	d ₂	
32	M10x1	6	3,5	30326003
40	M12x1	8	5	30326004
50	M16x1	10	6,4	30326005
63	M18x1	12	8	30326006
80	M20x1,5	14	10	30326007
100	M24x1,5	16	12	30326008

Blanking plugs

HSK	Dimensions			Order No.
	G	L	Wrench size	
32	M10x1	5,5	4	30326075
40	M12x1	7,5	5	30326076
50	M16x1	9,5	6	30326077
63	M18x1	11,5	8	30326078
80	M20x1,5	13,5	10	30326079
100	M24x1,5	15,5	12	30326074

Dimensions in mm.

Items included: Coolant tube with two O-rings and union nut.

Design: Free angular movement 1° self-centring, axially sealed.


Note: Designed in accordance with DIN 69895. Leak tested up to 80 bar.

Use: For sealing the threaded bore in HSK tool shanks if a coolant tube is not used.

Design: With Nylok insert for screw locking.

Material: Stainless steel.

Balancing gauges



HSK	Dimensions		Order No.
	L	H	
32	31	15	30326032
40	35	15	30326033
50	43	18	30326034
63	52	20	30326035
80	65	25	30326036
100	75	25	30326037


Use: For balancing HSK spindles and adapters as well as for sealing fast-rotating HSK spindles and adapters without a tool fitted.

Design: Permissible residual imbalance in accordance with DIN ISO 1940 part 1 quality G 2.5 at 8,000 min⁻¹

Material: Stainless steel.

Balancing value: G 2.5 at 8,000 min⁻¹

Blanking caps




HSK	Dimensions		Order No.
	L	H	
32	23	10	30326020
40	26	10	30326021
50	33	12,5	30326022
63	38	12,5	30326023
80	48	16	30326024
100	56	16	30326025

Use: For sealing spindle mountings without a tool fitted.

Design: Unbalanced.

Note: HSK balance gauges are recommended for sealing fast-rotating HSK adapters.




HSK	Dimensions			Order No.
	d ₁	L	H	
32	3	23	10	30326027
40	3	26	10	30326028
50	4	33	12,5	30326029
63	6	38	12,5	30326030
80	7	48	16	30326031
100	7	56	16	30326026

Dimensions in mm.

Use: For sealing spindle mountings without a tool fitted.

Design: Unbalanced, with central coolant bore.

Note: HSK balance gauges are recommended for sealing fast-rotating HSK adapters.





CONVERSION SYSTEMS AND ADAPTERS TO HSK-T

Introduction

Designation key	134
-----------------	-----

Conversion systems, adapters and blanks

KS flange adapters	136
Tool adapters	137
Extensions and reducers	152
Banks	153

HSK-T conversion systems make it possible to integrate the advantages of the HSK-T connection in an existing environment. Often the output and therefore the productivity in existing processes is not optimal, as the portion of non-productive times is too high. Non-productive times occur during the tool change necessary due to tool wear, however above all on re-tooling for different parts in variant production and small-scale series production.

The process can be specifically optimised in these cases using the conversion systems to HSK-T, as due to the high accuracy on changing the tools, times for setting up or breaking-in are practically not required.

Using the conversion systems almost all existing CNC machines can be converted easily, safely and cost-effectively to HSK-T by means of conversion adapters. Only information on the machine manufacturer, machine type and revolver type is required for the technical design of the necessary conversion adapters. All other technical data are known.

Designation key


Conversion systems and adapters to HSK-T connection

Conversion adapters


M	T	A	1	-	B	M	T	0	4	0	-	0	0	-	0	4	0
Series/type				Type of input				Connection and size				Connection index				HSK-T connection size	
MTA				1 Stationary				VDI								040 HSK-T40	
MAPAL Turning adapter				2 Driven				BMT								063 HSK-T63	
																100 HSK-T100	

KS flange adapter

K	S	-	V	L	-	M	O	D	1	0	0	-	H	S	K	-	T
Clamping unit				Adaptation				Shank Form and size				Adaptation Form and size					
KS				VL				Flange adapter				MOD				Module connection	
KS clamping cartridge												HSK-T				Hollow shank taper Form T	





Design		Characteristic		Connections		Direction of rotation		l_1 [mm]	l_2 [mm]
L	Long	N	Normal	E	Single	R	Right		
K	Short	Z	Set back	D	Double	L	Left		
				T	Triple				



Adaptation size		Projection length		Alignment		Internal cooling/MQL	
040	HSK-T40		l_1 [mm]	0	Without alignment	0	Without
063	HSK-T63			1	Radial alignment	1	Internal
100	HSK-T100			2	Radial and angular alignment	2	Lateral (SK)
						3	Internal and lateral combined
						4	With MQL (1-channel)
						5	With MQL (2-channels)
						6	With MQL (not specified)
						7	With MQL 1
						8	With MQL
						9	With high pressure HP

KS flange adapters

For turning applications



Module ø D	HSK-T	Design	Dimensions			Specification	Order No.
			d ₁	l ₁	l ₂		
68	40	links	45	25	44	KS-VL-MOD068-HSK-T040-025-01	30429656
68	40	rechts	45	25	44	KS-VL-MOD068-HSK-T040-025-01	30438946
102	63	links	70	37	72	KS-VL-MOD102-HSK-T063-037-01	30429657
102	63	rechts	70	37	72	KS-VL-MOD102-HSK-T063-037-01	30438947
165	100	links	110	55	112	KS-VL-MOD165-HSK-T100-055-01	30429658
165	100	rechts	110	55	112	KS-VL-MOD165-HSK-T100-055-01	30438948

Dimensions in mm.

Use: For fitting in the revolver and in conversion adapters for the manual clamping of HSK shanks on lathes.

Items included: Complete with KS clamping cartridge, sealing ring, eccentric pin and cylinder head screw.

Design: Can be exactly adjusted to the centre height by means of the actuating element in the flange adapter.


With internal coolant supply.

Note: You will find suitable KS clamping cartridges, sealing rings and angle setting gauges in the MAPAL catalogue Clamping.

In the section "Technical appendix" you will find information on the "right" and "left" designs and the fitting dimensions.

Tool adapters

Mori Seiki | NZ series



Mori Seiki NZ series

HSK-T	Dimensions											Specification	Order No.
	l ₁	l ₂	l ₃	l ₄	l ₅	l ₆	l ₇	l ₈	l ₉	l ₁₀	d ₁		
40	80	55	35	65	39	31	26	75	100	122	40	MTA1-BMT040-00-040KZDN-080-055	30432370

Dimensions in mm.

Use: For the modification of existing revolvers to HSK-T40.

Items included: Complete with basic holder and KS flange adapter.

Adjusted to lathe centre height.


Design: Basic holder suitable for the machines stated above. Double design.

It is possible to react to inaccuracies in the manufacturing peripherals by means of the actuating element in the KS flange adapter.

Note: You will find suitable KS clamping cartridges, sealing rings and angle setting gauges in the MAPAL catalogue Clamping.

Tool adapters

Mori Seiki | NL series



Mori Seiki NL series

HSK-T	Dimensions											Specification	Order No.
	l ₁	l ₂	l ₃	l ₄	l ₅	l ₆	l ₇	l ₈	l ₉	l ₁₀	d ₁		
63	107	70	60	65	54	51	37	20	80	116	60	MTA1-BMT060-00-063KNEN-107-070	30432368

Dimensions in mm.

Use: For the modification of existing revolvers to HSK-T63.

Items included: Complete with basic holder and KS flange adapter.

Adjusted to lathe centre height.



Design: Basic holder suitable for the machines stated above.

Can be used on both sides.

Note: You will find suitable KS clamping cartridges, sealing rings and angle setting gauges in the MAPAL catalogue Clamping.

Tool adapters

Gildemeister | CTX LZ (VDI30)



Gildemeister CTX LZ series (VDI 30 star revolver)

HSK-T	Dimensions										Design	Specification	Order No.
	l_1	l_2	l_3	l_4	l_5	l_6	l_7	l_8	l_9	d_1			
40	50	25	35	35	47	110	85	60	35	30	Left	MTA1-VDI030-00-040KZEL-050-025	30432360
40	50	25	35	35	47	110	85	60	35	30	Right	MTA1-VDI030-00-040KZER-050-025	30432353

Dimensions in mm.

Use: For the modification of existing revolvers to HSK-T40.

Items included: Complete with basic holder and KS flange adapter.

Adjusted to lathe centre height.

Design: Basic holder suitable for the machines stated above.



Left and right design. It is possible to react to inaccuracies in the manufacturing peripherals by means of the actuating element in the KS flange adapter.

Note: You will find suitable KS clamping cartridges, sealing rings and angle setting gauges in the MAPAL catalogue Clamping.

In the section "Technical appendix" you will find information on the "right" and "left" designs and the fitting dimensions.

Tool adapters

Gildemeister | CTX RLZ(VDI30)



Gildemeister CTX RLZ series (VDI 30 star revolver)

HSK-T	Dimensions											Design	Specification	Order No.
	l_1	l_2	l_3	l_4	l_5	l_6	l_7	l_8	l_9	l_{10}	d_1			
40	40	65	113	35	47	122,5	100	75	63	35	30	Right/left	MTA1-VDI30-00-040KZEN-040-065	30432359

Dimensions in mm.

Use: For the modification of existing revolvers to HSK-T40.

Items included: Complete with basic holder and KS flange adapter.

Adjusted to lathe centre height.



Design: Basic holder suitable for the machines stated above. Set back left/right design with double teeth. It is possible to react to inaccuracies in the manufacturing peripherals by means of the actuating element in the KS flange adapter.

Note: You will find suitable KS clamping cartridges, sealing rings and angle setting gauges in the MAPAL catalogue Clamping.

In the section "Technical appendix" you will find information on the "right" and "left" designs and the fitting dimensions.

Tool adapters

Gildemeister | CTX LZ (VDI40)



Gildemeister CTX LZ series (VDI 40 star revolver)

HSK-T	Dimensions										Design	Specification	Order No.
	l_1	l_2	l_3	l_4	l_5	l_6	l_7	l_8	l_9	d_1			
63	60	20	42,5	42,5	56	136	100	62	51	40	Right	MTA1-VDI040-00-063-KZER-060-020	30432364
63	60	20	42,5	42,5	56	136	100	62	51	40	Left	MTA1-VDI040-00-063-KZEL-060-020	30432351

Dimensions in mm.

Use: For the modification of existing revolvers to HSK-T63.

Items included: Complete with basic holder and KS flange adapter.

Adjusted to lathe centre height.

Design: Basic holder suitable for the machines stated above. Left and right design.



It is possible to react to inaccuracies in the manufacturing peripherals by means of the actuating element in the KS flange adapter.

Note: You will find suitable KS clamping cartridges, sealing rings and angle setting gauges in the MAPAL catalogue Clamping.

In the section "Technical appendix" you will find information on the "right" and "left" designs and the fitting dimensions.

Tool adapters

Gildemeister | CTX RLZ (VDI 40)



Gildemeister CTX RLZ series

HSK-T	Dimensions										Design	Specification	Order No.	
	l ₁	l ₂	l ₃	l ₄	l ₅	l ₆	l ₇	l ₈	l ₉	l ₁₀				
63	40	77	130	42,5	56	156	120	82	51	38	40	Right/left	MTA1-VDI040-00-063KZEN-040-077	30432357

Dimensions in mm.

Use: For the modification of existing revolvers to HSK-T63.

Items included: Complete with basic holder and KS flange adapter.

Adjusted to lathe centre height.


Design: Basic holder suitable for the machines stated above. Set back left/right design with double teeth. It is possible to react to inaccuracies in the manufacturing peripherals by means of the actuating element in the KS flange adapter.

Note: You will find suitable KS clamping cartridges, sealing rings and angle setting gauges in the MAPAL catalogue Clamping.


In the section "Technical appendix" you will find information on the "right" and "left" designs and the fitting dimensions.

Tool adapters

Index G200 | VDI 25 (w serration)



 Coolant outlets



Index G200 (VDI 25)

HSK-T	Dimensions									Design	Specification	Order No.
	l_1	l_2	l_3	l_4	l_5	l_6	l_7	l_8	d_1			
40	39	14	39	92	70	30	34	29	25	Right/left	MTA1-VDI025-00-040KZEN-039-014	30429575

Dimensions in mm.

Use: For the modification of existing revolvers to HSK-T40.

Items included: Complete with basic holder and KS flange adapter.

Adjusted to lathe centre height.



Design: Basic holder suitable for the machines stated above. Left/right design with double teeth. It is possible to react to inaccuracies in the manufacturing peripherals by means of the actuating element in the KS flange adapter.

Note: You will find suitable KS clamping cartridges, sealing rings and angle setting gauges in the MAPAL catalogue Clamping.

In the section "Technical appendix" you will find information on the "right" and "left" designs and the fitting dimensions.

Tool adapters

VDI axial



ISO 10889-1-80x124xHSK-T...

HSK-T	Dimensions						Specification	Order No.
	l ₁	l ₂	l ₃	l ₄	d ₁	D		
40	57	32	22	44	30	68	MTA1-VDI030-00-040KNEN-057-032	30432371
63	87	50	22	76	40	102	MTA1-VDI040-00-063KNEN-087-050	30432372
100	125	70	30	112	80	165	MTA1-VDI080-00-100KNEN-125-070	30432373

Dimensions in mm.

Use: For the modification of existing revolvers to HSK-T40, HSK-T63 and HSK-T100.

Items included: Complete with basic holder and KS flange adapter.

Adjusted to lathe centre height.

Design: Basic holder suitable for the machines stated above. Axial design.


It is possible to react to inaccuracies in the manufacturing peripherals by means of the actuating element in the KS flange adapter.

Note: You will find suitable KS clamping cartridges, sealing rings and angle setting gauges in the MAPAL catalogue Clamping.

In the section "Technical appendix" you will find information on the "right" and "left" designs and the fitting dimensions.

Tool adapters

Nakamura NTJ



Nakamura NTJ

HSK-T	Dimensions										Specification	Order No.
	l ₁	l ₂	l ₃	l ₄	l ₅	l ₆	l ₇	l ₈	l ₉	l ₁₀		
40	39,5	39,5	39,5	40	40	34	27	17	75	97	MTA1-NTJSON-00-040KZE-040-040	30429573

Dimensions in mm.

Use: For the modification of existing revolvers to HSK-T40.

Items included: Complete with basic holder and KS flange adapter.

Adjusted to lathe centre height. Basic holder suitable for the machines stated above.



It is possible to react to inaccuracies in the manufacturing peripherals by means of the actuating element in the KS flange adapter.

Note: You will find suitable KS clamping cartridges, sealing rings and angle setting gauges in the MAPAL catalogue Clamping.

In the section "Technical appendix" you will find information on the "right" and "left" designs and the fitting dimensions.

Tool adapters

Hardinge | T-42 axial



Hardinge T-42 (axial)

HSK-T	Dimensions					Specification	Order No.
	l_1	l_2	l_3	l_4	d_1		
40	53	28	37,5	37,5	44,9	MTA1-BMT045-00-040KNE-053-028	30437949

Dimensions in mm.

Use: For the modification of existing revolvers to HSK-T40.

Items included: Complete with basic holder and KS flange adapter.

Adjusted to lathe centre height.

Design: Basic holder suitable for the machines stated above.


It is possible to react to inaccuracies in the manufacturing peripherals by means of the actuating element in the KS flange adapter.

Note: You will find suitable KS clamping cartridges, sealing rings and angle setting gauges in the MAPAL catalogue Clamping.


In the section "Technical appendix" you will find information on the "right" and "left" designs and the fitting dimensions.

Tool adapters

Hardinge | T-42 radial



 Coolant outlets



Hardinge T-42 (radial)

HSK-T	Dimensions										Specification	Order No.
	l ₁	l ₂	l ₃	l ₄	l ₅	l ₆	l ₇	l ₈	l ₉	l ₁₀		
40	37,5	12,5	30	37,5	37,5	34	21	17	65	87	MTA1-HRDT42-00-040KZE-038-013	30559499

Dimensions in mm.

Use: For the modification of existing revolvers to HSK-T40.

Items included: Complete with basic holder and KS flange adapter.

Adjusted to lathe centre height.

Design: Basic holder suitable for the machines stated above.


It is possible to react to inaccuracies in the manufacturing peripherals by means of the actuating element in the KS flange adapter.

Note: You will find suitable KS clamping cartridges, sealing rings and angle setting gauges in the MAPAL catalogue Clamping.


In the section "Technical appendix" you will find information on the "right" and "left" designs and the fitting dimensions.

Tool adapters

Hardinge | T-51 SP axial



 Coolant outlets



Hardinge T-51 SP (axial)

HSK-T	Dimensions					Specification	Order No.
	l ₁	l ₂	l ₃	l ₄	d ₁		
63	43	25	42,5	42,5	55	MTA1-HRDT51-00-063KNE-043-025	30524879

Dimensions in mm.

Use: For the modification of existing revolvers to HSK-T63.

Items included: Complete with basic holder and KS flange adapter.

Adjusted to lathe centre height.

Design: Basic holder suitable for the machines stated above.


It is possible to react to inaccuracies in the manufacturing peripherals by means of the actuating element in the KS flange adapter.

Note: You will find suitable KS clamping cartridges, sealing rings and angle setting gauges in the MAPAL catalogue Clamping.


In the section "Technical appendix" you will find information on the "right" and "left" designs and the fitting dimensions.

Tool adapters

Hardinge | T-51 SP radial



 Coolant outlets



Hardinge T-51 SP (radial)

HSK-T	Dimensions										Specification	Order No.
	l ₁	l ₂	l ₃	l ₄	l ₅	l ₆	l ₇	l ₈	l ₉	l ₁₀		
63	97	60	100	45	42,5	51	37	25	45	136	MTA1-HRDT51-00-063KNE-097-060	30524881

Dimensions in mm.

Use: For the modification of existing revolvers to HSK-T63.

Items included: Complete with basic holder and KS flange adapter.

Adjusted to lathe centre height.

Design: Basic holder suitable for the machines stated above.



It is possible to react to inaccuracies in the manufacturing peripherals by means of the actuating element in the KS flange adapter.

Note: You will find suitable KS clamping cartridges, sealing rings and angle setting gauges in the MAPAL catalogue Clamping.

In the section "Technical appendix" you will find information on the "right" and "left" designs and the fitting dimensions.

Tool adapters

Hardinge | T-51 SP MSY



Hardinge T-51 SP MSY

HSK-T	Dimensions							Specification	Order No.
	l ₁	l ₂	l ₃	l ₄	l ₅	l ₆	l ₇		
63	67	30	30	35	42,5	114	78	MTA1-HRDT51-00-063KNE-067-030	30431643

Dimensions in mm.

Use: For the modification of existing revolvers to HSK-T63.

Items included: Complete with basic holder and KS flange adapter.

Adjusted to lathe centre height.

Design: Basic holder suitable for the machines stated above.


It is possible to react to inaccuracies in the manufacturing peripherals by means of the actuating element in the KS flange adapter.

Note: You will find suitable KS clamping cartridges, sealing rings and angle setting gauges in the MAPAL catalogue Clamping.

In the section "Technical appendix" you will find information on the "right" and "left" designs and the fitting dimensions.

Round shank adapters

With KS clamping and radial and angular alignment



HSK-T	Dimensions							Specification	Order No.
	d ₁	d ₂	d ₃	l ₁	l ₂	l ₃	l ₄		
40	50	32	6	128,5	90	38,5	30	KS-AD-ZYL032-HSK-T040-039-21	30439364
40	63	40	8	150	110	40	38	KS-AD-ZYL040-HSK-T040-040-21	30439366
63	80	40	10	192	140	52	38	KS-AD-ZYL040-HSK-T063-052-21	30440883
63	80	50	10	192	140	52	48	KS-AD-ZYL050-HSK-T063-052-21	30439368

Dimensions in mm.

Use: For fitting in boring bar holders for manual clamping of HSK shanks on lathes.

Items included: Complete with basic holder and KS flange adapter.


Design: Exactly adjustable by means of threaded pins and thrust pads (for aligning).

Note: You will find suitable KS clamping cartridges, sealing rings and angle setting gauges in the MAPAL catalogue Clamping.

Locating shank can be shortened to the required length.

HSK-T extensions


Shank HSK-T in accordance with ISO 1264-3



HSK-T	HSK-T d ₁	Dimensions		Weight kg	Specification	Order No.
		d ₂	l ₁			
40	40	45	60	0,5	KS-AD-HSK-T040-HSK-T040-060-01	30317312
40	40	45	80	0,7	KS-AD-HSK-T040-HSK-T040-080-01	30317310
63	63	70	120	2,3	KS-AD-HSK-T063-HSK-T063-120-01	30298734
63	63	70	80	1,7	KS-AD-HSK-T063-HSK-T063-080-01	30298733
100	100	110	120	6,3	KS-AD-HSK-T100-HSK-T100-120-01	30298737

HSK-T reducers

Shank HSK-T in accordance with ISO 1264-3



HSK-T	HSK-T d ₁	Dimensions			Weight kg	Specification	Order No.
		d ₂	l ₁	l ₂			
63	40	45	70	54	1,1	KS-AD-HSK-T063-HSK-T040-070-01	30317308
100	63	70	100	71	3,6	KS-AD-HSK-T100-HSK-T063-100-01	30298740
100	40	45	80	51	2,5	KS-AD-HSK-T100-HSK-T040-080-01	30317309

Dimensions in mm.

Items included: Complete with clamping cartridges and sealing ring, without coolant tube.


Design: Permissible run-out deviation on the hollow taper shank in relation to the internal taper = 0.005 mm.

Note: You will find suitable KS clamping cartridges, sealing rings and angle setting gauges in the MAPAL catalogue Clamping.

Balancing value: G 6.3 at 3,000 min⁻¹ as delivered.

HSK-T blanks

Shank HSK-T in accordance with ISO 12164-3



HSK-T	Dimensions			Specification	Order No.
	l_1	l_2	d_1		
40	55	35	54	OS-BL-HSK-T040-BLANK054-055-00	30308741
63	90	64	90	OS-BL-HSK-T063-BLANK090-090-00	30317098
63	210	184	72	OS-BL-HSK-T063-BLANK072-210-00	30317099
63	150	124	100	OS-BL-HSK-T063-BLANK100-150-00	30308742
100	100	71	110	OS-BL-HSK-T100-BLANK110-100-00	30308743
100	250	221	100	OS-BL-HSK-T100-BLANK100-250-00	30317101
100	160	131	120	OS-BL-HSK-T100-BLANK120-160-00	30317100


Dimensions in mm.


Design: Taper including collar hardened and finish ground.

Front part of blank not hardened or ground for further processing.

Items included: Without coolant tube.

Note: Excessive machining and any heat treatments of the completed blank may cause unacceptable distortion of the HSK shank. Claims against the warranty can therefore only be made for blanks that have not been processed.





TECHNICAL APPENDIX

HSK-T

Standard	156
Flanges	158
Description right/left design	159

VersaCut


Handling notes	160
----------------	-----

Cutting data

PcBN cutting materials	161
PCD cutting materials	161

HSK-T standard


For hollow shanks DIN 69893-1 HSK-T



HSK-T for automatic and manual tool change

		HSK size		
Nominal size	d ₁ h10	40	63	100
Taper diameter	d ₂	30.007	48.01	75.013
Shank length	L ₁ 0/-0.2	20	32	50
Slot width	b ₁ +/-0.04	8.05	12.54	20.02
Bore diameter	d ₈	4.6	7.5	12
Bore spacing	L ₈ +/-0.1	6	9	15
Flange width HSK-A	f ₁ 0/-0.1	20	26	29
Flange width HSK-C	f ₅	10	12.5	16
Additional for HSK-T				
Slot width	b ₂ +/-0.030	7.932	-	-
Slot width	b ₂ +/-0.0350	-	12.425	19.91

For adapters DIN 12164 HSK-T




HSK-T for automatic and manual tool change

		HSK size		
Nominal size	d ₁	40	63	100
Taper diameter	d ₂	29.998	47.998	74.997
Depth	L ₃ +0.2	14.4	22.4	35.4
Driving element width	b ₁ +/-0.05	7.8	12.3	19.78
Additional for HSK-C				
Bore diameter	d ₆	5	8	11
Bore spacing	L ₈ +/-0.1	6	9	15
Additional for HSK-T				
Driving element width	b ₂ -0.025	7.92	12.41	-
Driving element width	b ₂ -0.03	-	-	19.98

Dimensions in mm.

Addition to the HSK-T standard

In addition to the standard, the connection of driven tools using the HSK-T interface has been adopted.






The following definitions were also established in the HSK-T working group:

- Diameter of the drive shaft
- Drive shaft coupling type
- Position of the coupling
- Revolver wrench size
- Related HSK size
- Transfer point for cooling lubricants and barrier air
- Additional alignment feature for angled tool connections

General explanation, flanges


- The flanges are designed such that the direction of rotation during clamping is in the clockwise direction and releasing is always in the anti-clockwise direction.
- The flange design right is actuated on the side with the low driving element, the flange design left on the side with the high driving element.
- The location of the clamping cartridge and hence the flange design can be changed by moving the heavy-duty clamping pin to the opposite side.



HSK-T description left/right design


Revolver top:

- Clamping unit shank in revolver disc
- DIN-serration top
- Cutting head axis perpendicular to rotating axis
- Left design:
if shank left,
suitable for right tools
- Right design:
if shank right,
suitable for left tools




Revolver bottom:

- Clamping unit shank in revolver disc
- DIN-serration top
- Left design:
if shank left,
suitable for right tools
- Right design:
if shank right,
suitable for left tools



Shank position and position of the slots

(T = deep slot, F = shallow slot) as shown



Left design:

Cutting edge points to left,
Cutting force from above

Right design:

Cutting edge points to right,
Cutting force from above

Handling for VersaCut

Easier and quicker to insert change

For the special requirements of hard machining, for example grooving, groove turning or thread cutting, it is very important that the inserts are very stable. MAPAL relies on extremely stably clamped inserts on the grooving system VersaCut. The stability is ensured by a heavy clamping plate that presses the insert into a prismatic insert seat. To change the insert it is only necessary to undo the clamping plate using a hex-wrench. It is then possible to remove the insert from the prismatic insert seat and replace it.




Note: Only for trained personnel.




**Step 1:
Undo clamping**

Undo the threaded spindle using a hex-wrench until the insert can be removed easily from the prismatic insert seat.



**Step 2:
Remove insert**

Remove the insert from the prismatic insert seat.



**Step 3:
Clean connection**

Clean the prismatic insert seat using compressed air.



**Step 4:
Fit blade**

Push the new insert into the prismatic insert seat against the stop face. Then tighten the threaded spindle using a hex-wrench.



Discover tool and service solutions now that give you a lead:

REAMING | FINE BORING

DRILLING FROM THE SOLID | BORING | COUNTERSINKING

MILLING

TURNING

CLAMPING

ACTUATING

SETTING | MEASURING | DISPENSING

SERVICES